


52000077

AVENTICS Series 520 Mini-Spool Valves

The AVENTICS Series 520 is a line of solenoid air-operated, mini-spool valves that are ideal for piloting pneumatic cylinders. The valves have high-quality coils resistant to heat and moisture and suitable for high ambient temperatures and harsh environments. They can be mounted on joinable subbases for manifold applications. The AVENTICS 520 valves are suitable for automotive, case packing, packaging, and tire manufacturing applications.



Technical data

Industry	Industrial
Activation	Pneumatically
Valve type	Spool valve
Sealing principle	Soft seal
Connection type	Pipe connection

Compressed air connection input	G 1/8
Compressed air connection output	G 1/8

Nominal flow Qn	600 l/min
-----------------	-----------

Min. working pressure	1.5 bar
Max. working pressure	8 bar
Min. control pressure	1.5 bar
Max. control pressure	8 bar
Pilot	External
Min. ambient temperature	5 °C
Max. ambient temperature	50 °C
Medium	Compressed air

5/2-directional valve, Series 520

2023-11-13

52000077

Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	5 mg/m ³
Max. particle size	5 µm
Mounting screw	M3
Weight	0.065 kg

Material

Housing material	Aluminum, anodized
Seal material	Nitrile butadiene rubber
Material, front cover	Polyoxymethylene
Material threaded bushing	Aluminum
Part No.	52000077

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

5/2-directional valve, Series 520

2023-11-13

52000077

