

AVENTICS Series 580 Pneumatic Communications Node

The AVENTICS Series 580 fieldbus communications node supports up to 128 AVENTICS 500 Series solenoid valves per valve system in a compact package. It features an integrated graphic display for simple commissioning and display of diagnostic information. The 580 communication node mates to a variety of valve platforms including AVENTICS 501, 502 and 503 series. AVENTICS 580 Series communications nodes are ideal for use in automotive, tire, packaging, pharmaceutical processing, food and beverage, fine chemicals, and water/wastewater applications.



Technical data

Industry	Industrial
Fieldbus protocol	IO-Link
Note	Central fieldbus connection without I/O function Power supply plug M12x1, 4-pin
Signal connection E/A thread size	M12x1
Signal connection E/A number of poles	5-pin
Signal connection E/A coding	A-coded
Min. ambient temperature	-10 °C
Max. ambient temperature	50 °C
Max. number of solenoid coils	32
Max. number of valve positions	32
Operational voltage electronics	24 V DC
Electronics voltage tolerance	-10% / +10%
Current consumption electronics	0.04 A
Operating voltage, actuators	24 V DC
Total output for valves	4 A
Protection class	IP65
Diagnosis	Short circuit Overvoltage
Weight	0.298 kg

Material

Housing material
Part No.

Die-cast aluminum
P580AELM1010A00

Series 580

P580AELM1010A00

2024-05-17

Dimensions

