
AVENTICS Series CD02-AL Standardized valve systems (ISO 15407-1)

The AVENTICS Series CD02-AL complies with ISO 15407-1. The piloted controlled valves with a flow rate of up to 650 l/min consist of a robust aluminium body and are available with an individual connection plate as well as a valve system.





- Technical data Industry Activation Nominal flow Qn Compressed air connection output Min. working pressure Max. working pressure Electrical connection type Electrical connection size Sealing principle Pilot Standards Pilot valve width Valve type **Blocking principle** Connection type Return Compressed air connection input Compressed air connection, exhaust Compressed air connection pilot exhaust
- Industrial Electrically 450 l/min VDMA 02 base plate 1.5 bar 10 bar Plug ISO 15217, form C Soft seal Internal ISO 15407-1 15 mm Spool valve, positive overlapping Base plate principle, multiple Plate connection with spring/air spring return VDMA 02 base plate VDMA 02 base plate VDMA 02 base plate



5/2-directional valve, Series CD02-AL

0820038957

Basic valve equipment	Basic valve without pilot valve
Frame size	18 mm
Min. control pressure	1.5 bar
Max. control pressure	10 bar
Min. ambient temperature	0 °C
Max. ambient temperature	50 °C
Min. medium temperature	0°C
Max. medium temperature	60 °C
Medium	Compressed air
Max. particle size	5 µm
Min. oil content of compressed air	0 mg/m³
Max. oil content of compressed air	5 mg/m³
Connector standard	ISO 15217
Protection class with connection	IP65
Duty cycle	100 %
Mounting screws	M3
Weight	0.1 kg
Housing material	Aluminum
Seal material	Acrylonitrile butadiene rubber Hydrogenated acrylonitrile butadiene rubber
Material front plate	Polyamide
Part No.	0820038957

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in https://www.emerson.com/en-us/support).



5/2-directional valve, Series CD02-AL

0820038957

Dimensions

