
## **AVENTICS Series CD02-AL Standardized** valve systems (ISO 15407-1)

The AVENTICS Series CD02-AL complies with ISO 15407-1. The piloted controlled valves with a flow rate of up to 650 l/min consist of a robust aluminium body and are available with an individual connection plate as well as a valve system.





## Technical data

Industry Industrial
Activation Electrically
Nominal flow Qn 250 I/min

Version Pressurized Center
Compressed air connection output VDMA 02 base plate

Min. working pressure

Max. working pressure

Operational voltage

Operational voltage AC at 50 Hz

Operational voltage AC at 60 Hz

2.2 bar

10 bar

230 V AC

230 V

Voltage tolerance AC 50 Hz

Voltage tolerance AC 60 Hz

Manual override

-10% / +10%

without detent

Electrical connection 2
Electrical connection type Plug

Electrical connection size ISO 15217, form C

Sealing principle Soft seal
Pilot Internal
Standards ISO 15407-1

0820039260

Pilot valve width 15 mm

Valve type Spool valve, positive overlapping Blocking principle Base plate principle, multiple

Connection type Plate connection

Compressed air connection input VDMA 02 base plate

Compressed air connection, exhaust VDMA 02 base plate

Compressed air connection pilot exhaust VDMA 02 base plate

Holding power AC 50 Hz 1.6 VA Holding power AC 60 Hz 1.4 VA Switch-on power AC 50 Hz 2.2 VA Switch-on power AC 60 Hz 2 VA Frame size 18 mm Min. control pressure 2.2 bar 10 bar Max. control pressure 0°C Min. ambient temperature 50 °C Max. ambient temperature Min. medium temperature 0°C 60 °C Max. medium temperature

Medium Compressed air

Max. particle size  $5 \mu m$ Min. oil content of compressed air  $0 mg/m^3$ Max. oil content of compressed air  $5 mg/m^3$ Connector standard ISO 15217

Protection class with connection IP65

Duty cycle 100 %

Typ. switch-on time 9 ms

Typ. switch-off time 20 ms

Mounting screws M3

Weight 0.17 kg

Housing material Aluminum

Seal material Acrylonitrile butadiene rubber

Hydrogenated acrylonitrile butadiene rubber

Material front plate Polyamide
Part No. 0820039260

## Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in https://www.emerson.com/en-us/support).

## **Dimensions**

