

5/2-directional valve, Series CD04


R412013300

Series
CD04

2024-05-28

Series CD04

Qn = 900l/min



Technical data

Industry

Industrial

Activation

Pneumatically

Valve type

Spool valve, positive overlapping

Sealing principle

Soft seal

Connection type

Pipe connection

Standard compressed air connection

according to ANSI B1.20.3

Compressed air connection input

1/8-27 NPTF

Compressed air connection output

1/8-27 NPTF

Compressed air connection, exhaust

1/8-27 NPTF

Compressed air connection pilot input

1/8-27 NPTF

Nominal flow Qn

900 l/min

Min. working pressure

-0.95 bar

Max. working pressure

10 bar

Min. control pressure

2 bar

Max. control pressure

10 bar

Min. ambient temperature

-15 °C

5/2-directional valve, Series CD04

Series
CD04

R412013300

2024-05-28

Max. ambient temperature	65 °C
Min. medium temperature	-15 °C
Max. medium temperature	65 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	1 mg/m ³
Max. particle size	50 µm
Mounting on manifold strip	P-strip
Weight	0.3 kg

Material

Housing material	Die cast zinc Polyamide fiber-glass reinforced
Seal material	Acrylonitrile butadiene rubber
Part No.	R412013300

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

