R412011249

AVENTICS Series CON-MP Multipole plugs with cable

The AVENTICS Series CON-MP-with cable offers cables with a multipol plug like D-SUB with various numbers of pins and different length, optimized for our focused valve system Series like AV Also C/2 connectors for Valve systems of Series CL03 are available.



Technical data

Industry Industrial Type Multipole Cable with cable 24 V DC Operational voltage Max. operating voltage AC 24 V DC Electrical connection 1, type Socket Electrical connection 1, thread size D-Sub Electrical connection 1, number of poles 25-pin Cable exit 1 angled 90° Cable exit angle

Electrical connection 2, type open cable ends

Electrical connection 2, number of poles 25-pin Number of wires 25

Shielding unshielded

Cable length 5 m

Certificates UL (Underwriters Laboratories)

Protection class IP65
Min. ambient temperature -5 °C
Max. ambient temperature 50 °C

Multipole plug, series CON-MP

2024-04-02

R412011249

 $\begin{array}{ll} \text{Max. current} & 3 \text{ A} \\ \text{Wire cross-section} & 0.34 \text{ mm}^2 \\ \text{Cable-} \varnothing & 11.2 \text{ mm} \\ \text{Weight} & 1.065 \text{ kg} \end{array}$

Material

Housing material Polyamide

Material cable sheath Polyvinyl chloride Part No. R412011249

Technical information

The specified protection class is only valid in assembled and tested state.

Note for use with VS LP04: The plug can only be used in the LP04 versions with a side electrical connection.

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in https://www.emerson.com/en-us/support).

Fig. 2






Fig. 1



R412011249

PIN assignment and cable colors cable identification as per DIN 47100



Socket

D-Sub socket, 25 pin

D 0	ab sc	okot, zo pin
F	Pin	Color
	1	white
	2	brown
	3	green
	4	yellow
	5	gray
	6	pink
	7	blue
	8	red
	9	black
1	10	violet
•	11	gray/pink
1	12	red/blue
1	13	white/green
1	14	brown/green
1	15	white/yellow
1	16	yellow/brown
1	17	white/gray
1	18	gray/brown
1	19	white/pink
2	20	pink/brown
2	21	white/blue
2	22	brown/blue
2	23	white/red
2	24	brown/red
2	25	white/black