


Y-Plug connector, series CON-RD

R412021685

Adapter with cable



Technical data

Industry	Industrial
Type	Adapters & contact bridges
Cable	with cable
Operational voltage	48 V AC/DC
Operating voltage AC max.	48 V DC
Operating voltage DC, max.	48 V AC
Electrical connection 1, type	Plug
Electrical connection 1, thread size	M12x1
Electrical connection 1, number of poles	4-pin
Electrical connection 1, coding	A-coded
Cable exit	straight
Cable exit angle	180°
Electrical connection 2, type	Socket

Electrical connection 2, thread size	M8x1
Electrical connection 2, number of poles	3-pin
Electrical connection 2, coding	A-coded
Cable exit	straight
Cable exit angle	180°
Number of wires	3
Shielding	unshielded
Cable length	0.6 m
Protection class	IP67
Min. ambient temperature	-25 °C
Max. ambient temperature	80 °C
Max. current	4 A
Wire cross-section	0.25 mm ²
Cable-Ø	4.1 mm
Mounting screw tightening torque	0.8 Nm
Weight	0.064 kg


Material

Housing material	Polyurethane
Material cable sheath	Polyurethane
Part No.	R412021685

Technical information


The specified protection class is only valid in assembled and tested state.

Dimensions



L = length

Plug pin assignment



Pin assignment, socket

