

Blanking screw with O-ring, Series FPT

8639003800

Blanking
screws and
connectors

2024-11-13

AVENTICS Blanking screws and connectors



Technical data

| | |
|--------------------------------|-----------------|
| Industry | Industrial |
| Compressed air connection type | External thread |
| Port G | G 3/8 |
| Type | FPT-S-RBI |
| Min. working pressure | 0 bar |
| Max. working pressure | 16 bar |
| Min. ambient temperature | -20 °C |
| Max. ambient temperature | 80 °C |
| Delivery quantity | 25 piece |

Material


| | |
|---------------|--------------------------------|
| Material | Brass |
| Surface | nickel-plated |
| Seal material | Acrylonitrile butadiene rubber |
| Part No. | 8639003800 |

Dimensions

Blanking screw with O-ring, Series FPT

8639003800

2024-11-13



| Part No. | Port G | Ø E | H | L1 | SW1 |
|------------|--------|-----|-----|-----|-----|
| 8639000700 | M7 | 11 | 5.5 | 4 | 3 |
| 8639001800 | G 1/8 | 14 | 5.5 | 2.5 | 5 |
| 8639001400 | G 1/4 | 18 | 6.5 | 3.5 | 6 |
| 8639003800 | G 3/8 | 21 | 7.5 | 4 | 8 |
| 8639001200 | G 1/2 | 26 | 9 | 4 | 10 |