

AVENTICS Blanking screws and connectors



Technical data

| | |
|----------------------------------|-----------------|
| Industry | Industrial |
| Compressed air connection type | Internal thread |
| Port G | G 1/2 |
| Compressed air connection type 2 | External thread |
| Port D | R 1/2 |
| Type | FPT-S-RLT |
| Min. working pressure | 0 bar |
| Max. working pressure | 16 bar |
| Min. ambient temperature | -20 °C |
| Max. ambient temperature | 80 °C |
| Delivery unit | 5 piece |

Material


| | |
|----------|---------------|
| Material | Brass |
| Surface | nickel-plated |
| Part No. | 1823391754 |

Dimensions

Elbow fitting

2024-03-21

1823391754



| Part No. | Port D | Port G | H1 | H2 | L1 | L2 | SW |
|------------|--------|--------|------|-----|------|------|----|
| 1823391751 | R 1/8 | G 1/8 | 8.5 | 7 | 40 | 21 | 10 |
| 1823391752 | R 1/4 | G 1/4 | 11.5 | 9 | 49 | 25.5 | 13 |
| 1823391753 | R 3/8 | G 3/8 | 12.5 | 9.5 | 54.5 | 28 | 17 |
| 1823391754 | R 1/2 | G 1/2 | 13 | 13 | 64.5 | 33 | 21 |
| 1823391755 | R 3/4 | G 3/4 | 15 | 15 | 68.5 | 36.5 | 25 |
| 1823391756 | R 1 | G 1 | 17 | 17 | 84 | 45 | 30 |