

**AVENTICS Blanking screws and connectors**



**Technical data**

|                                  |                 |
|----------------------------------|-----------------|
| Industry                         | Industrial      |
| Compressed air connection type   | Internal thread |
| Port G                           | G 3/8           |
| Compressed air connection type 2 | External thread |
| Port D                           | R 3/8           |
| Type                             | FPT-S-RTT       |
| Min. working pressure            | 0 bar           |
| Max. working pressure            | 16 bar          |
| Min. ambient temperature         | -20 °C          |
| Max. ambient temperature         | 80 °C           |
| Delivery unit                    | 5 piece         |

**Material**


|          |               |
|----------|---------------|
| Material | Brass         |
| Surface  | nickel-plated |
| Part No. | 1823391747    |

**Dimensions**

# T-union

1823391747

2024-03-21



| Part No.   | Port D | Port G | H    | L    | L1 | SW |
|------------|--------|--------|------|------|----|----|
| 1823391745 | R 1/8  | G 1/8  | 8.2  | 19   | 42 | 10 |
| 1823391746 | R 1/4  | G 1/4  | 11   | 24   | 51 | 13 |
| 1823391747 | R 3/8  | G 3/8  | 11.5 | 26.5 | 56 | 17 |
| 1823391748 | R 1/2  | G 1/2  | 15   | 31.5 | 67 | 21 |
| 1823391749 | R 3/4  | G 3/4  | 16.5 | 32   | 73 | 25 |
| 1823391750 | R 1    | G 1    | 19   | 39   | 90 | 30 |