

AVENTICS Blanking screws and connectors



Technical data

| | |
|----------------------------------|-----------------|
| Industry | Industrial |
| Compressed air connection type | Internal thread |
| Port G | G 1 |
| Compressed air connection type 2 | External thread |
| Port D | R 1 |
| Type | FPT-S-RTT |
| Min. working pressure | 0 bar |
| Max. working pressure | 16 bar |
| Min. ambient temperature | -20 °C |
| Max. ambient temperature | 80 °C |
| Delivery unit | 2 piece |

Material


| | |
|----------|---------------|
| Material | Brass |
| Surface | nickel-plated |
| Part No. | 1823391750 |

Dimensions

T-union

1823391750

2024-03-21



| Part No. | Port D | Port G | H | L | L1 | SW |
|------------|--------|--------|------|------|----|----|
| 1823391745 | R 1/8 | G 1/8 | 8.2 | 19 | 42 | 10 |
| 1823391746 | R 1/4 | G 1/4 | 11 | 24 | 51 | 13 |
| 1823391747 | R 3/8 | G 3/8 | 11.5 | 26.5 | 56 | 17 |
| 1823391748 | R 1/2 | G 1/2 | 15 | 31.5 | 67 | 21 |
| 1823391749 | R 3/4 | G 3/4 | 16.5 | 32 | 73 | 25 |
| 1823391750 | R 1 | G 1 | 19 | 39 | 90 | 30 |