## **AVENTICS Series FSG Flat suction** grippers

AVENTICS Series FSG are round flat suction cups. FSG suction cups are the right choice for many standard applications with level, flat workpieces. Round, bellows suction cup with 2.5 folds for handling of extremely sensitive workpieces (optimum damping effect). Moreover, the special design of the folds permits use in systems with very short cycle times.





## Technical data

Industry Industrial Min. ambient temperature -10 °C Max. ambient temperature 70 °C -30 °C Temporary ambient temperature (<30 s) min. Temporary ambient temperature (<30 s) max. 120 °C Compressed air connection M5 external diameter 6 mm 1.2 N Holding force 0.008 cm<sup>3</sup> Volume Max. curving on object R min 8 mm

Abrasion value according to DIN 535 16  $100-120 \text{ mm}^3$  Hardness according to standard  $55 \pm 5 \text{ Shore A}$  Connection thread type Internal thread Material connector Aluminum


Suction unit material Acrylonitrile butadiene rubber

Delivery unit 2 piece
Weight 0.0014 kg
Part No. 1820455053

## **Technical information**

To be used on even and smooth to slightly rough surfaces.

## **Dimensions**



Part No.	ØD	G	Ha*)	Н	h	L	SW
1820455049	5	M5	15.6	16.5	6.5	8.5	8
1820455053	6	M5	15.5	16.5	6.5	8.8	8
1820455057	8	M5	15.6	17	7	8.5	8
1820455061	10	G 1/8	22.2	23.5	7.5	13	14

<sup>\*)</sup> Height for vacuum operation