

AVENTICS Series 580 Pneumatic Communications Node

The AVENTICS Series 580 fieldbus communications node supports up to 128 AVENTICS 500 Series solenoid valves per valve system in a compact package. It features an integrated graphic display for simple commissioning and display of diagnostic information. The 580 communication node mates to a variety of valve platforms including AVENTICS 501, 502 and 503 series. AVENTICS 580 Series communications nodes are ideal for use in automotive, tire, packaging, pharmaceutical processing, food and beverage, fine chemicals, and water/wastewater applications.



Technical data

Industry	Industrial
Fieldbus protocol	PROFIBUS DP
Note	Central fieldbus connection without I/O function Power supply plug M12x1, 5-pin class B
Min. ambient temperature	-10 °C
Max. ambient temperature	50 °C
Max. number of solenoid coils	128
Max. number of valve positions	110
Operational voltage electronics	24 V DC
Electronics voltage tolerance	-10% / +10%
Current consumption electronics	0.08 A
Operating voltage, actuators	24 V DC
Total output for valves	4 A
Protection class	IP65
Diagnosis	Short circuit Overvoltage
Electrical connection type	Plug (male)
Electrical connection size	M12
Electrical connection number of poles	5-pin

Series 580

2024-05-17

P580AEPT1010A00

Electrical connection coding

A-coded

Weight

0.326 kg

Material

Housing material

Die-cast aluminum

Part No.

P580AEPT1010A00

Series 580

P580AEPT1010A00

2024-05-17

