QR1-S-RSI standard series

R432000145

General series information AVENTICS Series QR1 Fittings

AVENTICS Series QR1 push-in connectors with easy, secure mounting are available in many versions: for tubing diameters from 3 to 16 mm, as well as in plastic, metal, and stainless steel variants. QR1 Series offers a cylindric thread that allows repeated connection and release without problems (Quick Release) and captive Oring guarantees an optimal sealing. Our QR program offers the right solution for every application and industry.



Technical data

Industry Fitting type Compressed air connection type Port G Compressed air connection type 2 Port D Type Working pressure min. Working pressure max Min. ambient temperature Max. ambient temperature Delivery unit Weight

Material

Surface Housing material Surface housing Industrial Bulkhead connector Internal thread 1/4 NPT push-in fitting Ø 3/8 QR1-S-RSI -0.95 bar 10 bar 0 °C 60 °C 10 piece 0.059 kg

nickel-plated Brass nickel-plated




Surface release ring holder Material thread Surface thread Part No. Acrylonitrile butadiene rubber Stainless Steel Polyoxymethylene Die cast zinc Brass nickel-plated Brass nickel-plated R432000145

Technical information

The series QR1 (plastic) and QR2 (metal) can not be combined These pneumatic components with NPT or inch thread dimensions are only available from our US sales organization.

Dimensions in inches



Dimensions in inches

| Part No. | Port D | Port G | М | А | В | С | E | F | SW |
|------------|--------|---------|----------|------|------|------|------|------|-------|
| R432000144 | Ø1/4 | 1/8 NPT | 9/16 UNF | 1.08 | 0.36 | 0.67 | 0.25 | 0.35 | 11/16 |
| R432000143 | Ø1/4 | 1/4 NPT | 9/16 UNF | 1.26 | 0.47 | 0.67 | 0.25 | 0.53 | 11/16 |
| R432000147 | Ø5/16 | 1/4 NPT | 5/8 UNF | 1.41 | 0.47 | 0.73 | 0.33 | 0.55 | 3/4 |
| R432000145 | Ø 3/8 | 1/4 NPT | 7/8 UNF | 1.4 | 0.47 | 0.83 | 0.23 | 0.55 | 1 |
| R432000149 | Ø5/16 | 3/8 NPT | 5/8 UNF | 1.45 | 0.51 | 0.73 | 0.33 | 0.59 | 3/4 |
| R432000146 | Ø 3/8 | 3/8 NPT | 7/8 UNF | 1.44 | 0.51 | 0.83 | 0.23 | 0.59 | 1 |
| R432000142 | Ø1/2 | 3/8 NPT | 7/8 UNF | 1.52 | 0.51 | 0.89 | 0.34 | 0.59 | 1 |

| Part No. | ØР |
|------------|------|
| R432000144 | 0.47 |
| R432000143 | 0.47 |



| Part No. | ØР |
|------------|------|
| R432000147 | 0.55 |
| R432000145 | 0.67 |
| R432000149 | 0.55 |
| R432000146 | 0.67 |
| R432000142 | 0.8 |

