QR1-S-RSI standard series

R432000146

General series information AVENTICS Series QR1 Fittings

AVENTICS Series QR1 push-in connectors with easy, secure mounting are available in many versions: for tubing diameters from 3 to 16 mm, as well as in plastic, metal, and stainless steel variants. QR1 Series offers a cylindric thread that allows repeated connection and release without problems (Quick Release) and captive Oring guarantees an optimal sealing. Our QR program offers the right solution for every application and industry.



Technical data

Industry Industrial

Fitting type Bulkhead connector
Compressed air connection type Internal thread

Port G 3/8 NPT

Compressed air connection type 2 push-in fitting

Port D Ø 3/8

Type QR1-S-RSI
Working pressure min. -0.95 bar
Working pressure max 10 bar
Min. ambient temperature 0 °C

Max. ambient temperature 60 °C

Delivery unit 10 piece

Weight 0.07 kg

Material

Surface nickel-plated

Housing material Brass

Surface housing nickel-plated



Seal material Acrylonitrile butadiene rubber

Material tooth lock washer Stainless Steel
Material release ring Polyoxymethylene

Material release ring holder Die cast zinc

Brass

Surface release ring holder nickel-plated

Brass

Surface thread nickel-plated Part No. R432000146


Technical information

Material thread

The series QR1 (plastic) and QR2 (metal) can not be combined

These pneumatic components with NPT or inch thread dimensions are only available from our US sales organization.

Dimensions in inches



Dimensions in inches

| Part No. | Port D | Port G | М | А | | С | | | SW |
|------------|--------|---------|----------|------|------|------|------|------|-------|
| R432000144 | Ø1/4 | 1/8 NPT | 9/16 UNF | 1.08 | 0.36 | 0.67 | 0.25 | 0.35 | 11/16 |
| R432000143 | Ø1/4 | 1/4 NPT | 9/16 UNF | 1.26 | 0.47 | 0.67 | 0.25 | 0.53 | 11/16 |
| R432000147 | Ø5/16 | 1/4 NPT | 5/8 UNF | 1.41 | 0.47 | 0.73 | 0.33 | 0.55 | 3/4 |
| R432000145 | Ø 3/8 | 1/4 NPT | 7/8 UNF | 1.4 | 0.47 | 0.83 | 0.23 | 0.55 | 1 |
| R432000149 | Ø5/16 | 3/8 NPT | 5/8 UNF | 1.45 | 0.51 | 0.73 | 0.33 | 0.59 | 3/4 |
| R432000146 | Ø 3/8 | 3/8 NPT | 7/8 UNF | 1.44 | 0.51 | 0.83 | 0.23 | 0.59 | 1 |
| R432000142 | Ø1/2 | 3/8 NPT | 7/8 UNF | 1.52 | 0.51 | 0.89 | 0.34 | 0.59 | 1 |

| Part No. | ØР |
|------------|------|
| R432000144 | 0.47 |
| R432000143 | 0.47 |



| Part No. | ØΡ |
|------------|------|
| R432000147 | 0.55 |
| R432000145 | 0.67 |
| R432000149 | 0.55 |
| R432000146 | 0.67 |
| R432000142 | 0.8 |

