QR1-S-RTT standard series

2122206140

General series information AVENTICS Series QR1 Fittings

■ AVENTICS Series QR1 push-in connectors with easy, secure mounting are available in many versions: for tubing diameters from 3 to 16 mm, as well as in plastic, metal, and stainless steel variants. QR1 Series offers a cylindric thread that allows repeated connection and release without problems (Quick Release) and captive Oring guarantees an optimal sealing. Our QR program offers the right solution for every application and industry.



Technical data

Industry Industrial Fitting type T-union

Compressed air connection type External thread

Port G G 1/4

Compressed air connection type 2 push-in fitting

Port D Ø 6

Type QR1-S-RTT

-1 bar Working pressure min. Working pressure max 16 bar -20 °C Min. ambient temperature 80 °C Max. ambient temperature -20 °C Min. medium temperature 80 °C Max. medium temperature Delivery unit 10 piece Weight 0.0218 kg

Material

Housing material Polyamide



Seal material	Acrylonitrile butadiene rubber
---------------	--------------------------------

Stainless Steel
Polyamide
Die cast zinc
nickel-plated

Material thread Brass

Surface thread nickel-plated Part No. 2122206140

Technical information

The series QR1 (plastic) and QR2 (metal) can not be combined Thread seal with captive O-ring

Dimensions in mm







