AVENTICS Series QR2 Fittings

AVENTICS Series QR2,push-in connectors with easy, secure mounting are available in many versions: In metal for tubing diameters from 3 to 16 mm. QR2 Series offers a cylindric thread that allows repeated connection and release without problems (Quick Release) and captive Oring guarantees an optimal sealing. Our QR program offers the right solution for every application and industry.



Technical data

Industry Industrial

Fitting type Straight plug connector

Compressed air connection type push-in fitting

Port G Ø 8

Compressed air connection type 2 push-in fitting

Port D Ø 8

Type QR2-F-RSK

Min. working pressure -0.95 bar
Max. working pressure 16 bar

Min. ambient temperature -20 °C Max. ambient temperature 150 °C

Delivery unit 10 piece

Weight 0.023 kg

Material

Housing material Brass

Surface housing nickel-plated

Seal material Fluorocaoutchouc

Material tooth lock washer Stainless Steel


1823386102

Material release ring
Surface release ring
Part No.

Brass
nickel-plated
1823386102

Technical information

The series QR1 (plastic) and QR2 (metal) can not be combined



Part No.	Port D	Port G	ØВ	ØС	ØE	L
1823386100	Ø 4	Ø 4	7	3	9	30
1823386101	Ø6	Ø6	10	5	11	31.5
1823386102	Ø8	Ø8	12	7	13	36
1823386103	Ø 10	Ø 10	13	9	15	37