

AVENTICS Series QR2 Fittings

AVENTICS Series QR2, push-in connectors with easy, secure mounting are available in many versions: In metal for tubing diameters from 3 to 16 mm. QR2 Series offers a cylindric thread that allows repeated connection and release without problems (Quick Release) and captive O-ring guarantees an optimal sealing. Our QR program offers the right solution for every application and industry.



Technical data

Industry	Industrial
Fitting type	Straight plug connector
Compressed air connection type	push-in fitting
Port G	Ø 14
Type	QR2-S-RSK
Min. working pressure	-0.95 bar
Max. working pressure	16 bar
Min. ambient temperature	-20 °C
Max. ambient temperature	80 °C
Delivery unit	5 piece
Weight	0.075 kg

Material


Housing material	Brass
Surface housing	nickel-plated
Seal material	Acrylonitrile butadiene rubber
Material tooth lock washer	Stainless Steel
Material release ring	Brass
Surface release ring	nickel-plated

Part No.


1823386083

Technical information

The series QR1 (plastic) and QR2 (metal) can not be combined



Dimensions for fitting with external thread



Part No.	Anschluss R	Port G	ØB	ØC	ØE	L
1823386077	–	Ø 4	7	3	9	30
1823386078	–	Ø 5	8	4	9.5	32
1823386079	–	Ø 6	10	5	11	31.5
1823386080	–	Ø 8	12	7	13	36
1823386081	–	Ø 10	13	9	15	37
1823386082	–	Ø 12	16	11	17	40.5
1823386083	–	Ø 14	18	12	20	45
R412010539	M28x1,5	Ø16	–	14	23	50