

5/2-directional valve, Series TC08, without detent, double solenoid

0820060651


Series
TC08

2024-10-17

- Excellent ratio of installation space and flow rate
- Large selection of electrical connections
- Electrical or pneumatic operated
- Long service life
- Adjustable coil with four 90° positions

AVENTICS Series TC08 Directional valves

The AVENTICS Series TC08/TC15 includes a wide range of spool valves with housings made of high-performance polymers with robust and flexible metal inserts. It is designed for flow rate performances from 800 to 1500 l/min. These directional valves are easy to assemble, making them ideal for applications requiring the highest efficiency in limited spaces.



Technical data

Industry	Industrial
Activation	Electrically
Valve type	Spool valve, positive overlapping
Switching principle	5/2, double solenoid
Actuating control	single
Sealing principle	Soft seal
Connection type	Pipe connection
Manual override	without detent
Compressed air connection input	G 1/8
Compressed air connection output	G 1/8
Compressed air connection, exhaust	G 1/8
Nominal flow Qn	800 l/min
Flow conductance b	0.36
Flow conductance C	3.5 l/(s*bar)
Min. working pressure	-0.9 bar
Max. working pressure	10 bar

5/2-directional valve, Series TC08, without detent, double solenoid

Series
TC08

2024-10-17

0820060651

Min. control pressure 2 bar

Max. control pressure 10 bar

Electrical connection type Plug
Electrical connection size ISO 15217, form C
Connector standard ISO 15217
Protection class with connection IP65
Operational voltage 24 V DC
Operational voltage DC 24 V
Voltage tolerance DC -10 % / +10 %

Pilot External
Coil width 15.6 mm
Pilot valve width 15 mm
Power consumption DC 2 W
Nominal resistance 280 Ω

Duty cycle 100 %
Typ. switch-on time 10 ms
Typ. switch-off time 10 ms

Min. ambient temperature -10 °C
Max. ambient temperature 50 °C
Min. medium temperature -10 °C
Max. medium temperature 50 °C
Medium Compressed air
Min. oil content of compressed air 0 mg/m³
Max. oil content of compressed air 5 mg/m³
Max. particle size 5 μm

Mounting on manifold strip P-strip
Mounting screw tightening torque 2 Nm
Weight 0.172 kg

Material

Housing material Polyamide fiber-glass reinforced
Seal material Acrylonitrile butadiene rubber
Polyurethane
Material threaded bushing Brass

5/2-directional valve, Series TC08, without detent, double solenoid

Series
TC08

2024-10-17

0820060651

Die cast zinc

Material front plate

Polyamide fiber-glass reinforced

Part No.

0820060651

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

5/2-directional valve, Series TC08, without detent, double solenoid

Series
TC08

2024-10-17

0820060651
Dimensions

Double Solenoid

