

## AVENTICS Series TRB Tie rod cylinders (ISO 15552)

The AVENTICS Series TRB (ISO 15552) cylinders are among the most frequently implemented in industries where heavy duty cylinders are required, such as wood and aluminium, steel and automotive, heavy-duty machinery and mining to name just a few.



### Technical data

|  |                                    |
|--|------------------------------------|
| Industry                               | Industrial                         |
| Standards                              | ISO 15552                          |
| Piston Ø                               | 63 mm                              |
| Stroke                                 | 50 mm                              |
| Ports                                  | G 3/8                              |
| Functional principle                   | Double-acting                      |
| Cushioning                             | Elastic cushioning                 |
| Magnetic piston                        | Piston with magnet                 |
| Environmental requirements             | Industry standard<br>ATEX optional |
| Piston rod thread - type               | External thread                    |
| Piston rod thread                      | M16x1,5                            |
| Piston rod                             | single                             |
| Scraper                                | Standard Industry Scraper          |
| Pressure for determining piston forces | 6,3 bar                            |
| Retracting piston force                | 1765 N                             |
| Extracting piston force                | 1960 N                             |
| Min. ambient temperature               | -20 °C                             |
| Max. ambient temperature               | 80 °C                              |
| Min. working pressure                  | 1.5 bar                            |

# Tie rod cylinder ISO 15552, Series TRB

series TRB

0822343601

2024-04-26

---

|                                    |                     |
|------------------------------------|---------------------|
| Max. working pressure              | 10 bar              |
| Impact energy                      | 1.6 J               |
| Weight 0 mm stroke                 | 1.4 kg              |
| Weight +10 mm stroke               | 0.052 kg            |
| Stroke max.                        | 2500 mm             |
| Medium                             | Compressed air      |
| Min. medium temperature            | -20 °C              |
| Max. medium temperature            | 80 °C               |
| Max. particle size                 | 50 µm               |
| Min. oil content of compressed air | 0 mg/m <sup>3</sup> |
| Max. oil content of compressed air | 5 mg/m <sup>3</sup> |

## Material

|                       |                      |
|-----------------------|----------------------|
| Piston rod            | Stainless Steel      |
| Scraper material      | Polyurethane         |
| Material tie-rod      | Steel, chrome-plated |
| Seal material         | Polyurethane         |
| Material, front cover | Die-cast aluminum    |
| Cylinder tube         | Aluminum             |
| End cover             | Die-cast aluminum    |
| Nut for piston rod    | Steel, chrome-plated |
| Part No.              | 0822343601           |

## Technical information

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the “Technical information” document (available in <https://www.emerson.com/en-us/support>).

# Tie rod cylinder ISO 1552, Series TRB

series TRB

0822343601

2024-04-26

## Dimensions



S = stroke

\*) For cylinders with optional piston rod with internal thread

| Piston Ø | A -2 | AF+1 | ØB d11 | ØBA d11 | BG min. | E    | EE    | G     | H    |
|----------|------|------|--------|---------|---------|------|-------|-------|------|
| 32       | 22   | 12   | 30     | 30      | 16      | 46.5 | G 1/8 | 27.75 | 47.5 |
| 40       | 24   | 13.5 | 35     | 35      | 16      | 53   | G 1/4 | 33.25 | 53   |
| 50       | 32   | 17   | 40     | 40      | 16      | 65   | G 1/4 | 31    | 65   |
| 63       | 32   | 17   | 45     | 45      | 16      | 75   | G 3/8 | 38.25 | 75   |
| 80       | 40   | 21   | 45     | 45      | 17      | 95   | G 3/8 | 38.25 | 95   |
| 100      | 40   | 21   | 55     | 55      | 17      | 115  | G 1/2 | 42.25 | 115  |
| 125      | 54   | 28   | 60     | 60      | 20      | 140  | G 1/2 | 53.85 | 140  |

| Piston Ø | KF  | KK       | KV | KW   | ØMM f8 | PL   | L2    | L3 ±0,5 | L8      |
|----------|-----|----------|----|------|--------|------|-------|---------|---------|
| 32       | M6  | M10x1,25 | 16 | 5    | 12     | 16   | 16.25 | 4.5     | 94±0,4  |
| 40       | M8  | M12x1,25 | 18 | 6    | 16     | 20   | 18.25 | 4.5     | 105±0,7 |
| 50       | M10 | M16x1,5  | 24 | 8    | 20     | 19   | 25    | 4.5     | 106±0,7 |
| 63       | M10 | M16x1,5  | 24 | 8    | 20     | 24   | 25    | 4.5     | 121±0,8 |
| 80       | M12 | M20x1,5  | 30 | 10   | 25     | 23.5 | 33    | 0       | 128±0,8 |
| 100      | M12 | M20x1,5  | 30 | 10   | 25     | 25   | 36    | 0       | 138±1   |
| 125      | M16 | M27x2    | 41 | 13.5 | 32     | 33   | 45    | 0       | 160±1   |

| Piston Ø | RT | SW | TG       | VA -1 | VD | WH     |
|----------|----|----|----------|-------|----|--------|
| 32       | M6 | 10 | 32.5±0,5 | 4     | 5  | 26±1,4 |
| 40       | M6 | 13 | 38±0,5   | 4     | 5  | 30±1,4 |

# Tie rod cylinder ISO 15552, Series TRB

0822343601

series TRB

2024-04-26

| Piston Ø | RT  | SW | TG       | VA -1 | VD | WH     |
|----------|-----|----|----------|-------|----|--------|
| 50       | M8  | 17 | 46,5±0,6 | 4     | 5  | 37±1,4 |
| 63       | M8  | 17 | 56,5±0,7 | 4     | 5  | 37±1,8 |
| 80       | M10 | 22 | 72±0,7   | 4     | 5  | 46±1,8 |
| 100      | M10 | 22 | 89±0,7   | 4     | 5  | 51±1,8 |
| 125      | M12 | 27 | 110±1,1  | 6     | 7  | 65±2,2 |

# Tie rod cylinder ISO 1552, Series TRB

series TRB

0822343601

2024-04-26

