



# 5/2-directional valve, Series 581, size 2

## 5812672650

ISO 5599-1, size 2, series 581

■  $Q_n = 2100 \dots 2700$  l/min



### Technical data

Industry

Industrial

Activation

Electrically

Nominal flow  $Q_n$

2700 l/min

Switching principle

5/2

Compressed air connection output

Base plate ISO 5599-1

Working pressure min.

-0.95 bar

Working pressure max

10 bar

DC operating voltage

24 V

Voltage tolerance DC

-10% / +10%

Manual override

with detent

without detent

Electrical connection type

Plug

Electrical connection size

EN 175301-803, form A

Sealing principle

Soft Seal

Pilot

External

Standards

ISO 5599-1

Pilot valve width

30x22 mm CNOMO

Valve type

Spool valve

Blocking principle

Single base plate principle

|   |   |
|---|---|
| Connection type<br>Plate connection                         | Max. particle size<br>50 µm                               |
| Return<br>with air spring return                            | Oil content of compressed air min.<br>0 mg/m <sup>3</sup> |
| Compressed air connection input<br>Base plate ISO 5599-1    | Oil content of compressed air max.<br>5 mg/m <sup>3</sup> |
| Compressed air connection, exhaust<br>Base plate ISO 5599-1 | Protection class with connection<br>IP65                  |
| Compressed air connection pilot exhaust<br>M5               | Compatibility index<br>14                                 |
| Power consumption DC<br>2 W                                 | Duty cycle<br>100 %                                       |
| Flow conductance C<br>10.8 l/(s*bar)                        | Typ. switch-on time<br>17 ms                              |
| Frame size<br>ISO 2   | Typ. switch-off time<br>40 ms                             |
| Control pressure min.<br>2.7 bar                            | mounting screws<br>with hexagon socket                    |
| Control pressure max.<br>10 bar                             | Mounting screw tightening torque<br>3.5 Nm                |
| Min. ambient temperature<br>-15 °C                          | Weight<br>0.56 kg   |
| Max. ambient temperature<br>50 °C                           | Housing material<br>Aluminum                              |
| Min. medium temperature<br>-15 °C                           | Seal material<br>Acrylonitrile butadiene rubber           |
| Max. medium temperature<br>50 °C                            | Part No.<br>5812672650                                    |
| Medium<br>Compressed air                                    |   |

## Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the “Technical information” document (available in <https://www.emerson.com/en-us/support>).

## Dimensions

