


# 5/3-directional valve, Series 581, size 2

## 5812462130

ISO 5599-1, size 2, series 581

- $Q_n = 2100 \dots 2700 \text{ l/min}$



### Technical data

Industry

Industrial

Activation

Electrically

Nominal flow  $Q_n$

2100 l/min

Switching principle

5/3

Version

Closed Center

Compressed air connection output

Base plate ISO 5599-1

Working pressure min.

-0.95 bar

Working pressure max

10 bar

DC operating voltage

24 V

Voltage tolerance DC

-10% / +10%

Manual override

without detent

Electrical connection type

Plug

Electrical connection size

ISO 15217, form C

Sealing principle

Soft Seal

|   |  |
|---|--|
| <b>Pilot</b><br>External  | <b>Min. medium temperature</b><br>-10 °C                         |
| <b>Standards</b><br>ISO 5599-1  | <b>Max. medium temperature</b><br>50 °C                          |
| <b>Pilot valve width</b><br>15 mm                                       | <b>Medium</b><br>Compressed air                                  |
| <b>Valve type</b><br>Spool valve  | <b>Max. particle size</b><br>50 µm                               |
| <b>Blocking principle</b><br>Single base plate principle                | <b>Oil content of compressed air min.</b><br>0 mg/m <sup>3</sup> |
| <b>Connection type</b><br>Plate connection                              | <b>Oil content of compressed air max.</b><br>5 mg/m <sup>3</sup> |
| <b>Compressed air connection input</b><br>Base plate ISO 5599-1         | <b>Protection class with connection</b><br>IP65                  |
| <b>Compressed air connection, exhaust</b><br>Base plate ISO 5599-1      | <b>Duty cycle</b><br>100 %                                       |
| <b>Compressed air connection pilot exhaust</b><br>Base plate ISO 5599-1 | <b>Typ. switch-on time</b><br>14 ms                              |
| <b>Power consumption DC</b><br>2 W                                      | <b>Typ. switch-off time</b><br>28 ms                             |
| <b>Flow conductance C</b><br>8.9 l/(s*bar)                              | <b>mounting screws</b><br>with hexagon socket                    |
| <b>Frame size</b><br>ISO 2  | <b>Mounting screw tightening torque</b><br>3.5 Nm                |
| <b>Control pressure min.</b><br>3 bar                                   | <b>Weight</b><br>0.33 kg   |
| <b>Control pressure max.</b><br>10 bar                                  | <b>Housing material</b><br>Polyamide fiber-glass reinforced      |
| <b>Min. ambient temperature</b><br>-10 °C                               | <b>Seal material</b><br>Acrylonitrile butadiene rubber           |
| <b>Max. ambient temperature</b><br>50 °C                                | <b>Part No.</b><br>5812462130                                    |

## Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the “Technical information” document (available in <https://www.emerson.com/en-us/support>).

## Dimensions

