
AVENTICS Series 581 - Size 1 Standardized valves

The AVENTICS series 581 complies with the ISO 5599-1 valve standard. Due to the high degree of modularity, the series offers all valve functions, integrated throttle valves, various pilot coils and an extensive range of accessories. Qn = $950 \dots 1400 \text{ l/min}$





Technical data Industry Activation Nominal flow Qn Switching principle Version Compressed air connection output Min. working pressure Max. working pressure Actuating control Sealing principle Pilot Standards Pilot valve width

Valve type Blocking principle Connection type Return Compressed air connection input Compressed air connection, exhaust Industrial Electrically 1100 l/min 5/3, closed center **Closed Center** Base plate ISO 5599-1 -0.95 bar 10 bar **Double Solenoid** Soft seal External Internal ISO 5599-1 30 mm Spool valve Single base plate principle Plate connection with air spring return Base plate ISO 5599-1 Base plate ISO 5599-1



5/3-directional valve, Series 581, size 1

5811480080

Flow conductance C	4.3 l/(s*bar)
Basic valve equipment	Basic valve without pilot valve
Frame size	ISO 1
Min. control pressure	3 bar
Max. control pressure	10 bar
Min. ambient temperature	-15 °C
Max. ambient temperature	50 °C
Min. medium temperature	-15 °C
Max. medium temperature	50 °C
Medium	Compressed air
Max. particle size	50 μm
Min. oil content of compressed air	0 mg/m³
Max. oil content of compressed air	5 mg/m³
Protection class with connection	IP65
Duty cycle	100 %
Mounting screws	with hexagon socket
Mounting screw tightening torque	2 Nm
Weight	0.21 kg
Housing material	Polyamide
Seal material	Acrylonitrile butadiene rubber
Part No.	5811480080

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in https://www.emerson.com/en-us/support).



5/3-directional valve, Series 581, size 1

5811480080

Dimensions

