# 5/2-directional valve, Series WV02

0820038602


Series WV02

2024-02-15

#### **Series WV02**

The AVENTICS Series WV02 spool valves with anodized aluminium housing feature short switching times and low switching pressures, while offering low power consumption due to a seal with low friction co-efficient.





#### Technical data

Industry Industrial Activation Electrically

Valve type Spool valve, positive overlapping

Sealing principle Soft seal

Connection type Pipe connection Manual override without detent

Compressed air connection input G 1/8
Compressed air connection output G 1/8

Nominal flow Qn 500 I/min

Min. working pressure1.5 barMax. working pressure10 barMin. control pressure1.5 barMax. control pressure10 bar

Electrical connection type Plug

Electrical connection size ISO 15217, form C

### 5/2-directional valve, Series WV02

0820038602

Series WV02

2024-02-15

Connector standard ISO 15217
Protection class with connection IP65
Operational voltage 24 V DC
Operational voltage DC 24 V

Voltage tolerance DC -10% / +10%

Pilot Internal
Coil width 15 mm
Pilot valve width 15 mm
Power consumption DC 2 W

Duty cycle 100 % Typ. switch-on time 8 ms

Min. ambient temperature 0 °C

Max. ambient temperature 50 °C

Min. medium temperature 0 °C

Max. medium temperature 60 °C

Medium Compressed air

Min. oil content of compressed air 0 mg/m³ Max. oil content of compressed air 5 mg/m³ Max. particle size 5  $\mu$ m

Mounting on manifold strip PRS strip

Mounting screws M3
Weight 0.16 kg

#### Material

Housing material Aluminum Surface housing anodized

Seal material Hydrogenated acrylonitrile butadiene rubber

Material threaded bushing Aluminum

Material front plate Polyamide

Part No. 0820038602

# 5/2-directional valve, Series WV02

0820038602

Series WV02

2024-02-15

### Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in https://www.emerson.com/en-us/support).

2024-02-15

### **Dimensions**

0820038602

