5/2-directional valve, Series WV02

0820038953

WV02


Series

2024-02-15

Series WV02

The AVENTICS Series WV02 spool valves with anodized aluminium housing feature short switching times and low switching pressures, while offering low power consumption due to a seal with low friction co-efficient.





Technical data

Industry Industrial Activation Electrically

Valve type Spool valve, positive overlapping

Basic valve equipment Basic valve without coil
Actuating control Single or Double Solenoid

Sealing principle Soft seal

Connection type Pipe connection

Compressed air connection input G 1/8
Compressed air connection output G 1/8

Nominal flow Qn 500 l/min

Min. working pressure1.5 barMax. working pressure10 barMin. control pressure1.5 barMax. control pressure10 bar

Electrical connection type Plug

5/2-directional valve, Series WV02

0820038953

Series WV02

2024-02-15

Electrical connection size ISO 15217, form C

Connector standard ISO 15217

Protection class with connection IP65

Pilot Internal
Coil width 15 mm
Pilot valve width 15 mm

Duty cycle 100 %

Min. ambient temperature 0 °C

Max. ambient temperature 50 °C

Min. medium temperature 0 °C

Max. medium temperature 60 °C

Medium Compressed air

Min. oil content of compressed air 0 mg/m³ Max. oil content of compressed air 5 mg/m³ Max. particle size 5 μ m

Mounting on manifold strip PRS strip

Mounting screws M3
Weight 0.1 kg

Material

Housing material Aluminum Surface housing anodized

Seal material Hydrogenated acrylonitrile butadiene rubber

Material threaded bushing Aluminum

Material front plate Polyamide

Part No. 0820038953

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in https://www.emerson.com/en-us/support).

0820038953 WV02 2024-02-15

Dimensions

