

# Stopper cylinder DFSP-32-25-PF-PA

Part number: 576113

FESTO



 General operating condition

## Data sheet

| Feature  | Value  |
|--|--|
| Stroke   | 25 mm  |
| Piston diameter                                      | 32 mm  |
| Piston rod thread                                    | M6   |
| Cushioning   | Elastic cushioning rings/pads at both ends                                   |
| Mounting position                                    | Any  |
| Mode of operation                                    | Single-acting<br>Pulling   |
| Structural design                                    | Piston<br>Piston rod<br>Profile barrel                                       |
| Position sensing                                     | For proximity sensor   |
| Piston rod end                                       | Internal thread  |
| Symbol   | 00991850   |
| Variants   | Internal thread on piston rod  |
| Protection against torsion/guide                     | Round piston rod   |
| Operating pressure                                   | 0.12 MPa ... 1 MPa   |
| Operating pressure                                   | 1.2 bar ... 10 bar   |
| Operating medium                                     | Compressed air as per ISO 8573-1:2010 [7:4:4]                                |
| Information on operating and pilot media             | Operation with oil lubrication possible (required for further use)           |
| Corrosion resistance class (CRC)                     | 2 - Moderate corrosion stress  |
| LABS (PWIS) conformity                               | VDMA24364-B1/B2-L  |
| Ambient temperature                                  | -10 °C ... 80 °C   |
| Permissible impact force on the advanced piston rod  | 3270 N   |
| Permissible lateral force during switching operation | 595 N  |
| Max. cycle rate                                      | 5 Hz   |
| Type of mounting                                     | Optionally:<br>With through-hole<br>With internal thread<br>With accessories |
| Pneumatic connection                                 | G1/8   |
| Note on materials                                    | RoHS-compliant   |
| Flange screws material                               | Steel, galvanized  |
| Cover material                                       | Wrought aluminum alloy<br>Anodized   |
| Seals material                                       | TPE-U(PU)  |
| Piston rod material                                  | High-alloy stainless steel   |
| Roller material                                      | Steel, galvanized  |

| Feature                     | Value                                     |
|-----------------------------|---|
| Material of cylinder barrel | Wrought aluminum alloy<br>Smooth anodized |