


# Mini slide DGSL-6-40-EA

Part number: 570164

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                    | Value  |
|--|--|
| Stroke                                     | 40 mm  |
| Adjustable end-position range/front length | 19 mm  |
| Adjustable end-position range/rear length  | 3.5 mm   |
| Piston diameter                            | 8 mm   |
| Drive unit operating mode                  | Yoke   |
| Cushioning                                 | Short elastic cushioning rings/pads at both ends                   |
| Mounting position                          | Any  |
| Guide                                      | Ball bearing cage guide  |
| Structural design                          | Yoke<br>Piston<br>Piston rod<br>Slide                              |
| Position sensing                           | For proximity sensor   |
| Symbol                                     | 00991263   |
| Operating pressure                         | 0.15 MPa ... 0.8 MPa   |
| Operating pressure                         | 1.5 bar ... 8 bar  |
| Max. speed                                 | 0.5 m/s  |
| Repetition accuracy                        | 0.3 mm   |
| Mode of operation                          | Double-acting  |
| Operating medium                           | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media   | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)           | 0 - No corrosion stress  |
| LABS (PWIS) conformity                     | VDMA24364-B1/B2-L  |
| Cleanroom class                            | Class 7 according to ISO 14644-1                                   |
| Ambient temperature                        | 0 °C ... 60 °C   |
| Impact energy in the end positions         | 0.05 J   |
| Cushioning length                          | 1.5 mm   |
| Max. force F <sub>y</sub>                  | 677 N  |
| Max. force F <sub>z</sub>                  | 677 N  |
| Max. torque M <sub>x</sub>                 | 8 Nm   |
| Max. torque M <sub>y</sub>                 | 5.5 Nm   |
| Max. torque M <sub>z</sub>                 | 5.5 Nm   |
| Theoretical force at 6 bar, retracting     | 23 N   |
| Theoretical force at 6 bar, advancing      | 30 N   |
| Moving mass                                | 90 g   |
| Product weight                             | 219 g  |

| <b>Feature</b>          | <b>Value</b>               |
|-------------------------|----------------------------|
| Alternative connections | See product drawing        |
| Type of mounting        | With through-hole          |
| Pneumatic connection    | M3                         |
| Note on materials       | RoHS-compliant             |
| Cover material          | Wrought aluminum alloy     |
| Seals material          | HNBR                       |
| Housing material        | Wrought aluminum alloy     |
| Piston rod material     | High-alloy stainless steel |