


# Parallel gripper DHPC-6-A-B

Part number: 8116738

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                       | Value  |
|---|--|
| Size  | 6  |
| Stroke per gripper jaw                        | 2 mm   |
| Max. interchangeability                       | 0.2 mm   |
| Max. gripper jaw angular play ax, ay          | 0 deg  |
| Max. gripper jaw backlash Sz                  | 0 mm   |
| Rotational symmetry                           | ≤0.2 mm  |
| Pneumatic gripper repetition accuracy         | ≤0.02 mm   |
| Number of gripper jaws                        | 2  |
| Actuator system                               | Pneumatic  |
| Mounting position                             | Any  |
| Mode of operation                             | Double-acting  |
| Gripper function                              | Parallel   |
| Gripping force backup                         | Without  |
| Structural design                             | Connection direction downwards<br>Lever<br>Standard mounting type for gripper fingers<br>Positively driven motion sequence   |
| Guide   | Ball guide   |
| Position sensing                              | For proximity sensor   |
| Symbol  | 00991894   |
| Variants                                      | Metals with copper, zinc or nickel by mass as main constituent are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils. |
| Operating pressure                            | 0.15 MPa ... 0.8 MPa   |
| Operating pressure                            | 1.5 bar ... 8 bar  |
| Operating pressure                            | 21.75 psi ... 116 psi  |
| Max. operating frequency of pneumatic gripper | 3 Hz   |
| Min. opening time at 6 bar                    | 9 ms   |
| Min. closing time at 6 bar                    | 11 ms  |
| Operating medium                              | Compressed air as per ISO 8573-1:2010 [7:4:4]  |
| Information on operating and pilot media      | Operation with oil lubrication possible (required for further use)   |
| Corrosion resistance class (CRC)              | 0 - No corrosion stress  |
| LABS (PWIS) conformity                        | VDMA24364-B2-L   |

| Feature  | Value   |
|--|---|
| Suitability for the production of Li-ion batteries | Metals with more than 1% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils |
| Ambient temperature                                | -10 °C ... 60 °C  |
| Gripping force per gripper jaw at 6 bar, opening   | 14.6 N  |
| Gripping force per gripper jaw at 6 bar, closing   | 11 N  |
| Gripping force per gripper jaw at 6 bar, opening   | 7.3 N   |
| Gripping force per gripper jaw at 6 bar, closing   | 5.5 N   |
| Mass moment of inertia                             | 0.011 kgcm <sup>2</sup>   |
| Maximum force on gripper jaw Fz, static            | 5 N   |
| Maximum torque on gripper jaw, Mx static           | 0.02 Nm   |
| Maximum torque on gripper jaw, My static           | 0.04 Nm   |
| Maximum torque on gripper jaw, Mz static           | 0.02 Nm   |
| Product weight                                     | 25 g  |
| Type of mounting                                   | Optionally:<br>Direct mounting via through-hole<br>Direct fastening via thread  |
| Pneumatic connection                               | M3  |
| Note on materials                                  | RoHS-compliant  |
| Housing material                                   | Aluminum, anodized  |
| Gripper jaw material                               | High-alloy stainless steel  |