

# Parallel gripper DHPS-6-A

Part number: 1254039

FESTO



 [General operating condition](#)

## Data sheet

Feature	Value
Size	6
Stroke per gripper jaw	2 mm
Max. interchangeability	≤0.2 mm
Max. gripper jaw angular play ax, ay	<1 deg
Max. gripper jaw backlash Sz	<0.02 mm
Rotational symmetry	≤0.2 mm
Pneumatic gripper repetition accuracy	<0.02 mm
Number of gripper jaws	2
Actuator system	Pneumatic
Mounting position	Any
Mode of operation	Double-acting
Gripper function	Parallel
Gripping force backup	Without
Structural design	Lever Positively driven motion sequence
Guide	Sliding guide
Position sensing	For Hall sensor
Symbol	00991894
Operating pressure	0.2 MPa ... 0.8 MPa
Operating pressure	2 bar ... 8 bar
Operating pressure	29 psi ... 116 psi
Max. operating frequency of pneumatic gripper	4 Hz
Min. opening time at 6 bar	8 ms
Min. closing time at 6 bar	17 ms
Max. mass per external gripper finger	10 g
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Metals with more than 5% by mass of copper are excluded from use. Exception are printed circuit boards, cables, electrical connectors and coils
Ambient temperature	5 °C ... 60 °C
Gripping force per gripper jaw at 6 bar, opening	30 N
Gripping force per gripper jaw at 6 bar, closing	25 N
Gripping force per gripper jaw at 6 bar, opening	15 N

Feature	Value
Gripping force per gripper jaw at 6 bar, closing	13.5 N
Mass moment of inertia	0.008 kgcm <sup>2</sup>
Maximum force on gripper jaw Fz, static	10 N
Maximum torque on gripper jaw, Mx static	0.5 Nm
Maximum torque on gripper jaw, My static	0.5 Nm
Maximum torque on gripper jaw, Mz static	0.5 Nm
Relubrication interval for guidance elements	10 MioCyc
Product weight	19 g
Type of mounting	Optionally: With internal thread and centering sleeve Via through-hole and centering sleeve
Pneumatic connection	M3
Note on materials	RoHS-compliant
Cover cap material	PA
Housing material	Wrought aluminum alloy, hard-anodized
Gripper jaw material	High-alloy stainless steel