

Electric linear slide EGSK-33-300-10P

Part number: 562780

FESTO



[PDF](#) General operating condition

Data sheet

| Feature | Value |
|--|---|
| Working stroke | 300 mm |
| Size | 33 |
| Reversing backlash | ≤20 μm |
| Screw diameter | 10 mm |
| Spindle pitch | 10 mm/U |
| Mounting position | Any |
| Guide | Recirculating ball bearing guide |
| Structural design | Electromechanical linear axis with ball screw drive |
| Homing | Reference switch |
| Spindle type | Ball screw drive |
| Symbol | 00991211 |
| Max. acceleration | 20 m/s ² |
| Max. speed | 0.79 m/s |
| Repetition accuracy | ±0.01 mm |
| Corrosion resistance class (CRC) | 0 - No corrosion stress |
| LABS (PWIS) conformity | VDMA24364 zone III |
| Degree of protection | IP10 |
| Ambient temperature | 0 °C ... 40 °C |
| Fixed bearing dynamic basic load rating | 1790 N |
| Linear guide dynamic basic load rating | 9207 N |
| Dynamic basic load rating, ball screw drive | 1760 N |
| 2nd moment of area Iy | 62000 mm ⁴ |
| 2nd moment of area Iz | 380000 mm ⁴ |
| Max. driving torque | 0.24 Nm |
| Max. force Fy | 2083 N |
| Max. force Fz | 2083 N |
| Max. torque Mx | 42.2 Nm |
| Max. torque My | 13.8 Nm |
| Max. torque Mz | 13.8 Nm |
| Max. feed force Fx | 148 N |
| No-load driving torque | 0.07 Nm |
| Ball screw drive statistical basic load rating | 2840 N |
| Linear guide statistical basic load rating | 20200 N |
| Mass moment of inertia JH per meter of stroke | 0.0771 kgcm ² |

| Feature | Value |
|---------------------------------------|------------------------------------|
| Mass moment of inertia JO | 0.0166 kgcm ² |
| Feed constant | 10 mm/U |
| Statistical fixed bearing load rating | 2590 N |
| Reference service life | 5000 km |
| Moving mass | 310 g |
| Slide weight | 310 g |
| Product weight | 3270 g |
| Additional slide weight | 310 g |
| Basic weight with 0 mm stroke | 1380 g |
| Additional weight per 10 mm stroke | 63 g |
| Type of mounting | With internal thread and dowel pin |
| Material of end caps | Die-cast aluminum Coated |
| Profile material | Coated High-alloy steel |
| Note on materials | RoHS-compliant |
| Drive cover material | Die-cast aluminum Coated |
| Slide material | Steel |
| Spindle nut material | Steel |
| Spindle material | Steel |