


Stepper motor EMMS-ST-57-S-SB-G2

Part number: 1370476

FESTO



 General operating condition

Data sheet

| Feature | Value |
|--|---|
| Ambient temperature | -10 °C ... 50 °C |
| Storage temperature | -20 °C ... 70 °C |
| Relative air humidity | 0 - 85 % |
| Conforms to standard | IEC 60034 |
| Insulation protection class | B |
| Thermal class according to EN 60034-1 | B |
| Rating class according to EN 60034-1 | S1 |
| Degree of protection | IP54 |
| Electrical connection technology | Plug |
| Note on materials | RoHS-compliant |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Certification | RCM compliance mark c UL us - Recognized (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive As per EU RoHS directive |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC To UK RoHS instructions |
| Nominal operating voltage DC | 48 V |
| Motor holding torque | 0.8 Nm |
| Max. rotational speed | 2720 rpm |
| Step angle with full step | 1.8 deg |
| Step angle tolerance | ±5% |
| Motor nominal current | 5 A |
| Voltage constant, phase | 12 mVmin |
| Phase winding resistance | 0.15 Ohm |
| Winding inductance phase | 0.5 mH |
| Rotor mass moment of inertia | 0.29 kgcm ² |
| Total output inertia moment | 0.3 kgcm ² |
| Product weight | 1090 g |
| Permissible axial shaft load | 10 N |
| Permissible radial shaft load | 52 N |
| Brake holding torque | 0.4 Nm |
| Brake DC operating voltage | 24 V |
| Brake power consumption | 8 W |
| Brake mass moment of inertia | 0.01 kgcm ² |