


Flanged pressure gauge FMA-63-0,25-C

Part number: 225783

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|--|--|
| Display range | 0 bar ... 0.25 bar |
| Display range | 0 psi ... 3.6 psi |
| Symbol | 00991463 |
| Conforms to standard | EN 837-3 |
| Pressure gauge nominal size | 63 |
| Explosion prevention and protection | Observe the information on the certificate Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX) |
| Type of mounting | Front panel mounting |
| Operating medium | Liquid media Gaseous media |
| Operating pressure | 0 bar ... 0.25 bar |
| Intermittent load factor | 0.9 |
| Continuous load factor | 0.75 |
| Measurement accuracy class | 1.6 |
| Degree of protection | IP43 |
| Temperature of medium | -20 °C ... 80 °C |
| Ambient temperature | -20 °C ... 60 °C |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Connection position | Centered on rear side |
| Pneumatic connection | G1/4 |
| Material of screwed plug | Brass |
| Housing material | Steel |
| Inspection window material | PMMA |
| Fastening ring material | Steel |
| Material of screws | Steel |
| Product weight | 120 g |
| Information on operating and pilot media | No acetylene No oxygen |