



# Exhaust air flow control valve GRE-1/2

Part number: 10353

FESTO



 [General operating condition](#)

## Data sheet

| Feature  | Value  |
|--|--|
| Valve function                                       | Sound pressure flow control function                               |
| Selection of additional function                     | with muffler   |
| Pneumatic connection 1                               | G1/2   |
| Adjusting element                                    | Slotted screw  |
| Type of mounting                                     | Screw-in   |
| Standard nominal flow rate in flow control direction | 3600 l/min   |
| Standard flow rate 6->0 bar                          | 0 l/min ... 4300 l/min   |
| Operating pressure                                   | 0 bar ... 10 bar   |
| Ambient temperature                                  | -10 °C ... 70 °C   |
| Mounting position                                    | Any  |
| Symbol   | 00991451   |
| Operating medium                                     | Compressed air as per ISO 8573-1:2010 [7:-:-]                      |
| Information on operating and pilot media             | Operation with oil lubrication possible (required for further use) |
| LABS (PWIS) conformity                               | VDMA24364-B1/B2-L  |
| Temperature of medium                                | -10 °C ... 70 °C   |
| Product weight                                       | 75 g   |
| Material of screwed plug                             | Wrought aluminum alloy   |
| Note on materials                                    | RoHS-compliant   |
| Seals material                                       | NBR  |
| Material of adjusting screw                          | Brass  |