

Non return valve H-3/4-B

Part number: 11692

FESTO



Data sheet

 General operating condition

| Feature | Value |
|---------------------------------------|---|
| Valve function | Non-return function |
| Pneumatic connection 1 | G3/4 |
| Pneumatic connection 2 | G3/4 |
| Type of mounting | Screw-in |
| Operating pressure | 0.04 MPa ... 1.2 MPa |
| Operating pressure | 0.4 bar ... 12 bar |
| Ambient temperature | -10 °C ... 60 °C |
| Housing material | Wrought aluminum alloy, anodized |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Mounting position | Any |
| Symbol | 00991455 |
| Standard nominal flow rate 1->2 (6-5) | 5900 l/min |

| Feature | Value |
|--|--|
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Storage temperature | -10 °C ... 60 °C |
| Temperature of medium | -10 °C ... 60 °C |
| Pilot medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Max. tightening torque | 60 Nm |
| Product weight | 101 g |
| Note on materials | RoHS-compliant |
| Seals material | NBR |