
## **Proportional pressure control valve MPPES-3-1/8-6-010** Part number: 187352

## (î)



General operating condition

## Data sheet

| Feature                                      | Value  |
|--|--|
| Nominal width pressurization                 | 3 mm   |
| Exhaust nominal width                        | 2 mm   |
| Actuation type                               | Electrical   |
| Sealing principle                            | Soft   |
| Mounting position                            | Any  |
| Structural design                            | Directly controlled piston regulator   |
| Short-circuit protection                     | For all electrical connections   |
| Safety instructions                          | MPPES safety position: if the power supply cable breaks, the outlet pressure will drop to 0 bar. |
| Symbol                                       | 00995305   |
| Reverse polarity protection                  | for all electrical connections   |
| Valve function                               | 3-way proportional pressure control valve closed   |
| Operating pressure                           | ≤0.8 MPa   |
| Operating pressure                           | ≤8 bar   |
| Pressure regulation range MPa                | 0 MPa 0.6 MPa  |
| Pressure regulation range                    | 0 bar 6 bar  |
| Inlet pressure 1                             | 7 bar 8 bar  |
| Inlet pressure 1 MPa                         | 0.7 MPa 0.8 MPa  |
| Max. pressure hysteresis                     | 0.001 MPa  |
| Max. pressure hysteresis                     | 0.01 bar   |
| Switching time off                           | 280 ms   |
| On switching time                            | 210 ms   |
| DC operating voltage range                   | 18 V 30 V  |
| Nominal operating voltage DC                 | 24 V   |
| Residual ripple                              | 10 %   |
| Setpoint/actual values                       | Voltage type 0 - 10 V  |
| Operating medium                             | Compressed air as per ISO 8573-1:2010 [7:4:4]<br>Inert gas                                       |
| Information on operating and pilot media     | Operation with oil lubrication possible (required for further use)                               |
| Certification                                | RCM compliance mark  |
| KC characters                                | KC EMC   |
| CE marking (see declaration of conformity)   | As per EU EMC directive<br>As per EU RoHS directive  |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC<br>To UK RoHS instructions  |

**FESTO** 

| Feature                          | Value   |
|----------------------------------|---|
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress                                 |
| LABS (PWIS) conformity           | VDMA24364-B2-L  |
| Temperature of medium            | 0 °C 60 °C  |
| Degree of protection             | IP65  |
| Ambient temperature              | 0 °C 50 °C  |
| Product weight                   | 915 g   |
| Electrical connection            | 8-pin<br>M16x0.75<br>Plug<br>as per DIN 45326<br>Round design |
| Type of mounting                 | With through-hole   |
| Pneumatic connection 1           | G1/8  |
| Pneumatic connection 2           | G1/8  |
| Pneumatic connection 3           | G1/8  |
| Note on materials                | RoHS-compliant  |
| Housing material                 | Wrought aluminum alloy  |
| Diaphragm material               | NBR   |