


# Filter regulator MS6-LFR-1/4-D7-CRV-AS

Part number: 529206

FESTO



 General operating condition

## Data sheet

| Feature                          | Value  |
|----------------------------------|--|
| Size                             | 6  |
| Series                           | MS   |
| Actuator lock                    | Rotary knob with detent<br>can be closed with accessories  |
| Mounting position                | Vertical +/- 5°  |
| Grade of filtration              | 5 µm   |
| Condensate drain                 | Fully automatic<br>Manual, non-detenting                   |
| Structural design                | Filter regulator with pressure gauge                       |
| Max. condensate volume           | 38 ml  |
| Controller function              | Outlet pressure constant<br>With secondary exhausting      |
| Bowl guard                       | Plastic bowl guard   |
| Degree of condensate separation  | >75 %  |
| Symbol                           | 00991587   |
| Pressure gauge                   | with pressure gauge  |
| Operating pressure               | 0.2 MPa ... 1.2 MPa  |
| Operating pressure               | 2 bar ... 12 bar   |
| Pressure regulation range        | 0.5 bar ... 12 bar   |
| Max. pressure hysteresis         | 0.025 MPa  |
| Max. pressure hysteresis         | 0.25 bar   |
| Max. pressure hysteresis         | 3.625 psi  |
| Standard nominal flow rate       | 2200 l/min   |
| Operating medium                 | Compressed air as per ISO 8573-1:2010 [7:4:-]<br>Inert gas |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress                              |
| LABS (PWIS) conformity           | VDMA24364-B1/B2-L  |
| Storage temperature              | -10 °C ... 60 °C   |
| For use in the food industry     | See supplementary material information                     |
| Air quality class at the output  | Compressed air as per ISO 8573-1:2010 [6:4:4]              |
| Temperature of medium            | -10 °C ... 60 °C   |
| Ambient temperature              | -10 °C ... 60 °C   |
| Pore size                        | <5 µm  |
| Product weight                   | 875 g  |

| Feature                        | Value  |
|--------------------------------|--|
| Type of mounting               | Optionally:<br>Front panel mounting<br>Line installation<br>With accessories |
| Pneumatic connection 1         | G1/4   |
| Pneumatic connection 2         | G1/4   |
| Note on materials              | RoHS-compliant   |
| Material of operator panel     | PA<br>POM  |
| Seals material                 | NBR  |
| Compressed air filter material | PE   |
| Housing material               | Die-cast aluminum  |
| Diaphragm material             | NBR  |
| Material of bowl               | PC   |
| Separating disc material       | POM  |