



# Air preparation combination unit MSB6-1/2:C3J4D1A1F3-WP

FESTO

Part number: 542287



 [General operating condition](#)

## Data sheet

| Feature                                  | Value  |
|--|--|
| Size                                     | 6  |
| Series                                   | MS   |
| Actuator lock                            | Rotary knob with detent<br>can be closed with accessories  |
| Mounting position                        | Vertical +/- 5°  |
| Grade of filtration                      | 5 µm   |
| Condensate drain                         | Fully automatic  |
| Structural design                        | Branching module<br>Soft start valve<br>Pressure switch<br>Shut off valve<br>Filter regulator with pressure gauge        |
| Controller function                      | Outlet pressure constant<br>With primary pressure compensation<br>With secondary exhausting<br>With return flow function |
| Bowl guard                               | Plastic bowl guard   |
| Symbol                                   | 00991760   |
| Pressure gauge                           | with pressure gauge  |
| Operating pressure                       | 4,5 bar ... 12 bar   |
| Pressure regulation range                | 4 bar ... 12 bar   |
| Standard nominal flow rate               | 3000 l/min   |
| Coil characteristics                     | 24 V DC: 1.5 W   |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]<br>Inert gas   |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use)   |
| Corrosion resistance class (CRC)         | 2 - Moderate corrosion stress  |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L  |
| Storage temperature                      | -10 °C ... 60 °C   |
| For use in the food industry             | See supplementary material information   |
| Air quality class at the output          | Compressed air as per ISO 8573-1:2010 [6:4:4]  |
| Temperature of medium                    | 5 °C ... 60 °C   |
| Ambient temperature                      | 5 °C ... 60 °C   |
| Product weight                           | 3500 g   |
| Type of mounting                         | With accessories   |
| Pneumatic connection 1                   | G1/2   |
| Pneumatic connection 2                   | G1/2   |
| Pneumatic connection 3                   | G1/2   |

| <b>Feature</b>    | <b>Value</b>      |
|-------------------|-------------------|
| Note on materials | RoHS-compliant    |
| Housing material  | Die-cast aluminum |
| Material of bowl  | PC                |