Energy efficiency module MSE6-D2M-5000-CBUS-S-RG-BAR-VCB-AGD

FESTO

Part number: 8085453



General operating condition

Data sheet

Size Series Mounting position Valve function Reset method Operating pressure Operating pressure Operating pressure Pressure regulation range MPa	6 MSE Horizontal +/- 5° 2/2, open, monostable Mechanical spring 0.35 MPa 1.3 MPa 3.5 bar 13 bar 50.75 psi 188.5 psi 0.25 MPa 1 MPa
Mounting position Valve function Reset method Operating pressure Operating pressure Operating pressure	Horizontal +/- 5° 2/2, open, monostable Mechanical spring 0.35 MPa 1.3 MPa 3.5 bar 13 bar 50.75 psi 188.5 psi 0.25 MPa 1 MPa
Valve function Reset method Operating pressure Operating pressure Operating pressure	2/2, open, monostable Mechanical spring 0.35 MPa 1.3 MPa 3.5 bar 13 bar 50.75 psi 188.5 psi 0.25 MPa 1 MPa
Reset method Operating pressure Operating pressure Operating pressure	Mechanical spring 0.35 MPa 1.3 MPa 3.5 bar 13 bar 50.75 psi 188.5 psi 0.25 MPa 1 MPa
Operating pressure Operating pressure Operating pressure	0.35 MPa 1.3 MPa 3.5 bar 13 bar 50.75 psi 188.5 psi 0.25 MPa 1 MPa
Operating pressure Operating pressure	3.5 bar 13 bar 50.75 psi 188.5 psi 0.25 MPa 1 MPa
Operating pressure	50.75 psi 188.5 psi 0.25 MPa 1 MPa
,	0.25 MPa 1 MPa
Pressure regulation range MPa	-
·	
Pressure regulation range	2.5 bar 10 bar
Pressure regulation range psi	36.25 psi 145 psi
Max. pressure hysteresis	0.03 MPa
Max. pressure hysteresis	0.3 bar
Max. pressure hysteresis	4.35 psi
Standard nominal flow rate	4500 l/min
Duty cycle	100%
Max. load current consumption	≤0.1 A
Logic max. current consumption	≤0.25 A
Certification	RCM compliance mark
KC characters	KC EMC
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication not possible
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Storage temperature	-10 °C 60 °C
Temperature of medium	0 ℃ 50 ℃
Degree of protection	IP65 With plug socket
Ambient temperature	0 ℃ 50 ℃
Product weight	2700 g
Pneumatic connection 1	G1/2
Pneumatic connection 2	G1/2
Seals material	NBR

Feature	Value
Housing material	Die-cast aluminum
Covering material	PA-reinforced
Cover material	PA-reinforced
Operating voltage range DC electronics/sensors	18 V 30 V
DC load voltage operating voltage range	18 V 28.8 V
Reverse polarity protection	for operating voltage connections
Displayable unit(s)	kPa l l/min m3 mbar psi scf scfm
Flow measuring range start value	50 l/min
Flow measuring range end value	5000 l/min
Accuracy of flow rate	± (3% o.m.v. + 0.3% FS)
Pressure measuring range initial value	0 MPa
Pressure measuring range initial value	0 bar
Pressure measuring range initial value	0 psi
Pressure measuring range end value	1.4 MPa
Pressure measuring range end value	14 bar
Pressure measuring range end value	203 psi
Accuracy in ± % FS	3 %FS