


Push-in L-connector NPQH-L-Q6-E-P10

Part number: 578271

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|-------------------------------------------------|---------------------------------------------------------------------------|
| Size | Standard |
| Nominal width | 5 mm |
| Tubing insertion depth | 15.8 mm |
| Mounting position | Any |
| Design | L-shape |
| Pack size | 10 |
| Structural design | Push-pull principle |
| Symbol | 00997424 |
| Operating pressure for entire temperature range | -0.095 MPa ... 2 MPa |
| Operating pressure for entire temperature range | -0.95 bar ... 20 bar |
| Operating pressure for entire temperature range | -13.775 psi ... 290 psi |
| Information on operating pressure | Water: max. 0.6 MPa at 0 - 50 °C |
| Certificate issuing authority | NSF C0523185 |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:-:-] Water (liquid, ice-free) |
| Information on operating and pilot media | Operation with oil lubrication possible |
| Corrosion resistance class (CRC) | 3 - High corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Cleanroom class | Class 4 according to ISO 14644-1 |
| For use in the food industry | See declaration of conformity NSF/ANSI 169 |
| Ambient temperature | 0 °C ... 150 °C |
| Product weight | 17.2 g |
| Pneumatic connection 1 | For pneumatic tubing outside diameter 6 mm |
| Pneumatic connection 2 | for pneumatic tubing outside diameter 6 mm |
| Note on materials | RoHS-compliant |
| Housing material | Brass, chemically nickel-plated |
| Guard ring material | PEI |
| Releasing ring material | Brass, chemically nickel-plated |
| Material of tubing seal | FPM |
| Material of tube retaining claw | High-alloy stainless steel |
| Thrust ring material | PEI |