


Flanged pressure gauge PAGN-P-63-0.1M-G14-1-CPA

Part number: 8178632

FESTO



[PDF](#) General operating condition

Data sheet

| Feature | Value |
|--|------------------------------|
| Display range | 0 MPa ... 0.1 MPa |
| Symbol | 00991463 |
| Conforms to standard | EN 837-3 |
| Pressure gauge nominal size | 63 |
| Structural design | Bourdon tube pressure gauge |
| Type of mounting | Front panel mounting |
| Operating medium | Inert gas Neutral liquids |
| Operating pressure | 0 MPa ... 0.1 MPa |
| Operating pressure | 0 bar ... 1 bar |
| Operating pressure | 0 psi ... 14.5 psi |
| Intermittent load factor | 0.66 |
| Measurement accuracy class | 1 |
| Degree of protection | IP43 |
| Storage temperature | -40 °C ... 70 °C |
| Temperature of medium | -20 °C ... 60 °C |
| Ambient temperature | -20 °C ... 60 °C |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Note on materials | RoHS-compliant |
| Connection position | Centered on rear side |
| Pneumatic connection | G1/4 |
| Materials in contact with the media | Brass |
| Material of screwed plug | Brass |
| Housing material | ABS |
| Inspection window material | SAN |
| Fastening ring material | Steel |
| Material of screws | Steel |
| Housing colour | Black |
| Product weight | 120 g |
| Information on operating and pilot media | No acetylene No oxygen |

| Feature | Value |
|---------|--------------------------------|
| Scale | Single scale MPa (external) |