


# Pressure sensor SPAU-P10R-H-Q4D-L-PNLK-PNVBA-M8D

Part number: 8001211

FESTO



General operating condition

## Data sheet

| Feature                                      | Value  |
|--|--|
| Symbol                                       | 00995410   |
| Certification                                | RCM compliance mark<br>c UL us - Listed (OL)               |
| CE marking (see declaration of conformity)   | As per EU EMC directive<br>As per EU RoHS directive        |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC<br>To UK RoHS instructions      |
| KC characters                                | KC EMC   |
| Note on materials                            | RoHS-compliant   |
| Measured variable                            | Relative pressure  |
| Method of measurement                        | Piezoresistive pressure sensor                             |
| Pressure measuring range initial value       | 0 MPa  |
| Pressure measuring range initial value       | 0 bar  |
| Pressure measuring range initial value       | 0 psi  |
| Pressure measuring range end value           | 1 MPa  |
| Pressure measuring range end value           | 10 bar   |
| Pressure measuring range end value           | 145 psi  |
| Max. overload pressure                       | 15 bar   |
| Overload pressure                            | 1.5 MPa  |
| Overload pressure                            | 15 bar   |
| Overload pressure                            | 217.5 psi  |
| Operating medium                             | Compressed air as per ISO 8573-1:2010 [7:4:4]<br>Inert gas |
| Information on operating and pilot media     | Operation with oil lubrication possible                    |
| Temperature of medium                        | 0 °C ... 50 °C   |
| Ambient temperature                          | 0 °C ... 50 °C   |
| ADC resolution                               | 12 bit   |
| Accuracy in ± % FS                           | 1.5 %FS  |
| Repetition accuracy in ± %FS                 | 0.3 %FS  |
| Temperature co-efficient in ± %FS/K          | 0.05 %FS/K   |
| Switching output                             | 2 x PNP or 2 x NPN switchable                              |
| Switching function                           | Freely programmable  |
| Switching element function                   | N/C contact/N/O contact switchable                         |
| Max. output current                          | 100 mA   |
| Analog output                                | 0 - 10 V<br>4 - 20 mA<br>1 - 5 V                           |

| Feature   | Value  |
|---|--|
| Rise time   | 3 ms   |
| Max. load resistance of current output                | 500 Ohm  |
| Min. load resistance of voltage output                | 10 kOhm  |
| Short-circuit protection                              | yes  |
| Protocol  | IO-Link®   |
| IO-Link®, protocol version                            | Device V 1.1   |
| IO-Link®, profile                                     | Smart sensor profile   |
| IO-Link®, function classes                            | Binary data channel (BDC)<br>Process data variable (PDV)<br>Identification<br>Diagnostics<br>Teach channel |
| IO-Link®, communication mode                          | COM2 (38,4 kBd)  |
| IO-Link®, SIO mode support                            | Yes  |
| IO-Link®, port class                                  | A  |
| IO-Link®, process data width OUT                      | 0 Byte   |
| IO-Link®, process data width IN                       | 2 Byte   |
| IO-Link®, process data content IN                     | 14 bit PDV (pressure measurement)<br>2 bit BDC (pressure monitoring)                                       |
| IO-Link®, minimum cycle time                          | 3 ms   |
| IO-Link®, data memory required                        | 500 byte   |
| DC operating voltage range                            | 20 V ... 30 V  |
| Reverse polarity protection                           | for all electrical connections   |
| Electrical connection 1, connection type              | Plug   |
| Electrical connection 1, connection technology        | M8x1 A-coded as per EN 61076-2-104   |
| Electrical connection 1, number of pins/wires         | 4  |
| Electrical connection for input 1, connection pattern | 00991171   |
| Type of mounting                                      | With H-rail  |
| Mounting position                                     | Any  |
| Pneumatic connection                                  | QS-4   |
| Product weight  | 65 g   |
| Display type  | Illuminated LCD  |
| Displayable unit(s)                                   | MPa<br>bar<br>inH2O<br>inHg<br>kPa<br>kgf/cm <sup>2</sup><br>mmHg<br>psi                                   |
| Setting options                                       | IO-Link®<br>Teach-in<br>Via display and pushbuttons  |
| Protection against tampering                          | IO-Link®<br>PIN code   |
| Setting range threshold value                         | 0 % ... 100 %  |
| Setting range hysteresis                              | 0 % ... 90 %   |
| Degree of protection                                  | IP65<br>IP67   |
| Corrosion resistance class (CRC)                      | 2 - Moderate corrosion stress  |
| LABS (PWIS) conformity                                | VDMA24364-B1/B2-L  |