
One-way flow control valve VFOE-LE-T-R18-Q6-F1A Part number: 8157639

FESTO





General operating condition

Data sheet

| Feature | Value |
|--|--|
| Valve function | Exhaust air flow control non-return function |
| Pneumatic connection 1 | QS-6 |
| Pneumatic connection 2 | R1/8 |
| Actuation type | Manual |
| Adjusting element | Rotary knob with detent |
| Type of mounting | Screw-in |
| Standard nominal flow rate in flow control direction | 165 l/min |
| Standard nominal flow rate in non-return direction | 110 l/min 200 l/min |
| Ambient temperature | -10 °C 60 °C |
| Housing material | PBT |
| Explosion prevention and protection | Observe the information on the certificate Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX) |
| Mounting position | Any |
| Symbol | 00991452 |
| Width across flats | 13 mm |
| Rotatability | 360 deg/continuous swiveling not permissible |
| Variants | Metals with copper, zinc or nickel by mass as main constituent are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils. |
| Operating pressure for entire temperature range | 0.02 MPa 1 MPa |
| Operating pressure for entire temperature range | 0.2 bar 10 bar |
| Operating pressure for entire temperature range | 2.9 psi 145 psi |
| Standard flow rate in flow control direction 6 -> 0 bar | 280 l/min |
| Standard flow rate in non-return direction at 6 -> 0 bar | 300 l/min 360 l/min |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| LABS (PWIS) conformity | VDMA24364 zone III |

| Feature | Value |
|--|---|
| Suitability for the production of Li-ion batteries | Metals with more than 1% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils |
| Cleanroom class | Class 4 according to ISO 14644-1 |
| Temperature of medium | -10 °C 60 °C |
| Product weight | 9.5 g |
| Note on materials | RoHS-compliant |
| Cover material | РВТ |
| Material of dynamic seals | HNBR |
| Threaded bolt material | Steel, chemically nickel-plated |
| Releasing ring material | PBT |
| Static seal material | NBR |