Angle seat valve VZXA-B-TS6-25-M2-V13T-23-K-75-20-V4

FESTO

Part number: 8060531





General operating condition

Data sheet

Value
Poppet valve with piston actuator
Pneumatic
Any
Line installation
Threaded sleeve G1 as per DIN ISO 228
2/2
Non-reversible
0 MPa 2.3 MPa
0 bar 23 bar
Mechanical spring
Externally controlled
Internal thread G1/8
0.5 MPa 1 MPa
5 bar 10 bar
72.5 psi 145 psi
00995586
Vapor Hydraulic fluid based on mineral oil Inert gas Mineral oil Water Filtered compressed air, 200 µm filter mesh Neutral liquids
Under valve seat, for gaseous and liquid media
On/off mode
Compressed air as per ISO 8573-1:2010 [7:4:4]
600 mm ² /s
-10 °C 180 °C
0 °C 60 °C
22.6 m³/h
Weather-protected locations class C1 based on IEC 60654-1
RoHS-compliant
VDMA24244 III
VDMA24364 zone III

Feature	Value
Material number, fitting housing	1.4409
Seals material	FPM
Spindle seal material	PTFE
Seat seal material	PTFE
Product weight	3600 g
Certification	CRN
Explosion prevention and protection	Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)
Certificate issuing authority	German Technical Control Board (TÜV) 968/V 1039.01/20
Safety integrity level (SIL)	SIL 2
PFH	1.36E-7
PFD	5.95E-4
Actuator size	75 mm
Stroke	20 mm
Control function	Closed by spring force, NC
Position sensing	With mechanical indicator
Drive housing material	Cast stainless steel
Material number, drive housing	1.4408
Storage temperature	-10 °C 60 °C
Degree of protection	IP65 IP67
Piston rod material	High-alloy stainless steel
Cover material	Cast stainless steel