



ALDIS-L50001AC

Automated Load Detect Ident System

GATEWAY SYSTEMS

SICK
Sensor Intelligence.



Ordering information

Type	Part no.
ALDIS-L50001AC	1139251

Included in delivery: CLV650-0120 (1), TDC-E210AC (1)

Other models and accessories → www.sick.com/Automated_Load_Detect_Ident_System



Detailed technical data

Features

Product category	Gateway and cloud solutions
Fields of application	Indoor area
Identification technology	Laser-based code reading

Mechanics/electronics

Supply voltage	24 V DC (9 V DC ... 36 V DC)
Power consumption	2.4 W
Housing dimensions (W x D x H)	162 mm x 32 mm x 128 mm
Housing material	Polyamide PA6
Housing color	Light blue (RAL 5012)
Enclosure rating	IP20 (according to DIN EN 60529)
Connections	<ul style="list-style-type: none"> Molex 1x 14 pin connector (PWR, DIOs and Analog-Inputs) Molex 1x 20 pin connector (additional DIOs, 1-wire, RS-232, RS-422/485/SSI, CAN A, CAN B) Ethernet 1x ETH0 Ethernet 1x ETH1 USB 2.0 1x type A SMA 2x antenna connector MCX 1x antenna connector USB 1 x Micro-B (on board)

Performance

Sensor	Acceleration sensor, Magnetometer, Thermometers
Internal computer	1 GB, DD3, dual-core Cortex-A7 with Cortex-M4 co-processor
Internal memory	16 GB
Operating system	Linux and Micro Services
Ecosystem	Docker
User interface	TDC-E Device Manager, User Manager, Interface Manager, Portainer, TEMS Web interface
Data protocol	MQTT REST API
Data format	JSON

Connectivity	Mobile communication (4G) WLAN LAN
Mobile network	Global coverage, LTE TDD: 1900/2300/2500/2600, LTE-FDD: 700/800/850/900/1700/1800/1900/2100/2600, UMTS: 850/900/1700/1900/2100
Region of use	North America, Latin American

Interfaces

GPS	✓
Protocol	GPS, GLONASS, BeiDo, Galileo
Electrical connection	MCX
Modem	✓, 4G
Data transmission rate	(≤ 150 Mbit/s), Full 4G performance cannot be guaranteed on operating temperature over 60 °C.
Ethernet	✓ (2)
Data transmission rate	(10 Mbit/s ... 1,000 Mbit/s)
Electrical connection	RJ45
WLAN	✓
Data transmission rate	(≤ 65 Mbit/s), single band 2.4 GHz
Protocol	IEEE 802.11 b/g/n
Serial	✓, RS-232
Electrical connection	Micro-Fit (20-pin)
CAN bus	✓ (2)
Data transmission rate	1 Mbit/s, adjustable
Protocol	J1939, CANOpen
Electrical connection	Micro-Fit (20-pin)
Inputs/outputs	I/O 6 analog inputs (configurable, current and voltage), 6 digital inputs/outputs (configurable), 2 additional digital inputs, 2 additional digital outputs ¹⁾
Optical indicators	3, LED, status displays
Configuration interface	Web-Interface REST API

¹⁾ Analog measurement of voltage (0 - 36 V) with an accuracy of $\pm(0.2\%+30 \text{ mV})$, current (0 - 32 mA), with an accuracy of $\pm(1\%+0.1 \text{ mA})$, input resistance 27.5 k Ω typical for voltage mode, 100 Ω typical for current mode.

Ambient data

Ambient temperature, operation	0 °C ... +40 °C
Ambient temperature, storage	-20 °C ... +70 °C
Electromagnetic compatibility (EMC)	EN 303446-1 EN 55032 EN 55024 EN 61000-3-2 EN 61000-3-3
Product safety	EN 62311:2008
Radio approval	RED

General notes

Description	The gateway system enables bidirectional communication between industrial equipment and automated guided vehicle systems.
--------------------	---

ALDIS-L50001AC | Automated Load Detect Ident System

GATEWAY SYSTEMS

Items supplied	TDC-E210AC with ALDIS software module, CLV650 fixed mount barcode scanner
-----------------------	---

Classifications

ECLASS 6.0	19179090
ECLASS 6.2	19179090
ECLASS 7.0	19179090
ECLASS 8.0	19179090
ECLASS 8.1	19179090
ECLASS 9.0	19179090
ECLASS 10.0	19179090
ECLASS 11.0	19179090
ECLASS 12.0	19179090
UNSPSC 16.0901	43222605

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com