

# DOL-1205-G12MQ

Industrial Ethernet cables and fieldbus cables



### DOL-1205-G12MQ | Industrial Ethernet cables and fieldbus cables



### Ordering information

Туре	Part no.
DOL-1205-G12MQ	6032636

Other models and accessories -> www.sick.com/Industrial\_Ethernet\_cables\_and\_fieldbus\_cables


#### Detailed technical data

Technical specifications	
Connection type head A	Female connector, M12, 5-pin, straight, B-coded
Connection type head B	Flying leads
Connection type	Flying leads
Connector material	TPU
Connector color	Black
Locking nut material	CuZn, nickel-plated brass
Tightening torque	0.5 Nm
Cable	12 m, 2-wire, PUR, halogen-free
Jacket material	PUR, halogen-free
Jacket color	Violet
Cable diameter	7.6 mm
Conductor cross section	2 x 0.34 mm <sup>2</sup>
Shielding	Shielded
Bending radius	
Flexible use	> 10 x cable diameter
Stationary position	> 5 x cable diameter
Bending cycles	≥ 1,000,000
Bending cycles	
Bending cycles	≥ 1,000,000
Bending cycles Reference voltage	≥ 1,000,000 ≤ 60 V
Bending cycles Reference voltage Rated impulse voltage	≥ 1,000,000 ≤ 60 V 1.5 kV
Bending cycles Reference voltage Rated impulse voltage Current loading	≥ 1,000,000 ≤ 60 V 1.5 kV 4 A
Bending cycles Reference voltage Rated impulse voltage Current loading Traversing speed	≥ 1,000,000 ≤ 60 V 1.5 kV 4 A 3 m/s
Bending cycles Reference voltage Rated impulse voltage Current loading Traversing speed Travelling distance	≥ 1,000,000 ≤ 60 V 1.5 kV 4 A 3 m/s 5 m
Bending cycles Reference voltage Rated impulse voltage Current loading Traversing speed Travelling distance Acceleration	≥ 1,000,000 ≤ 60 V 1.5 kV 4 A 3 m/s 5 m ≤ 5 m/s <sup>2</sup>
Bending cycles Reference voltage Rated impulse voltage Current loading Traversing speed Travelling distance Acceleration Signal type	≥ 1,000,000 ≤ 60 V 1.5 kV 4 A 3 m/s 5 m ≤ 5 m/s² PROFIBUS DP
Bending cycles Reference voltage Rated impulse voltage Current loading Traversing speed Travelling distance Acceleration Signal type Special feature	<ul> <li>≥ 1,000,000</li> <li>≤ 60 V</li> <li>1.5 kV</li> <li>4 A</li> <li>3 m/s</li> <li>5 m</li> <li>≤ 5 m/s<sup>2</sup></li> <li>PROFIBUS DP</li> <li>Twisted pair</li> </ul>
Bending cycles Reference voltage Rated impulse voltage Current loading Traversing speed Travelling distance Acceleration Signal type Special feature Application	≥ 1,000,000 < 60 V 1.5 kV 4 A 3 m/s 5 m ≤ 5 m/s² PROFIBUS DP Twisted pair Zones with oils and lubricants
Bending cycles Reference voltage Rated impulse voltage Current loading Traversing speed Travelling distance Acceleration Signal type Special feature Application Enclosure rating Operating temperature	≥ 1,000,000 ≤ 60 V 1.5 kV 4 A 3 m/s 5 m ≤ 5 m/s² PROFIBUS DP Twisted pair Zones with oils and lubricants IP67

### DOL-1205-G12MQ | Industrial Ethernet cables and fieldbus cables

Drag chain operation	-25 °C +60 °C
Head	-25 °C +85 °C
Classifications	
ECLASS 5.0	19030312
ECLASS 5.1.4	19030312
ECLASS 6.0	27060304
ECLASS 6.2	27060304
ECLASS 7.0	27060304
ECLASS 8.0	27060304
ECLASS 8.1	27060304
ECLASS 9.0	27060304
ECLASS 10.0	27060304
ECLASS 11.0	27060304
ECLASS 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

#### Dimensional drawing (Dimensions in mm (inch))



# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

