

FXO-GETCO0000

Flexi Soft

SAFETY CONTROLLERS





Ordering information

| Fieldbus, industrial network | Туре | Part no. |
|------------------------------|---------------|----------|
| EtherCAT [®] | FX0-GETC00000 | 1051432 |

Other models and accessories → www.sick.com/Flexi_Soft











Detailed technical data

Features

| Module | Gateway |
|------------------------------|--|
| Fieldbus, industrial network | EtherCAT® |
| Configuration method | Via software (Flexi Soft Designer, Safe EFI-pro System: Safety Designer) |

Interfaces

| Fieldbus, industrial network | EtherCAT [®] |
|------------------------------|---|
| Data transmission rate | 10 Mbit/s, 10Base-T 100 Mbit/s, 100Base-T autosensing |
| Connection type | 2 x female connector, RJ-45 |

Electrical data

| Protection class | III (EN 61140) |
|----------------------------|--------------------|
| Voltage supply | Via FLEXBUS+ |
| Internal power consumption | \leq 3 W $^{1)}$ |

¹⁾ Via FLEXBUS+.

Mechanical data

| Dimensions (W x H x D) | 22.5 mm x 96.5 mm x 120.6 mm |
|------------------------|------------------------------|
| Weight | 150 g (± 10 %) |

Ambient data

| Enclosure rating | IP20 (EN 60529) |
|-------------------------------|------------------------|
| Ambient operating temperature | -25 °C +55 °C |
| Storage temperature | -25 °C +70 °C |
| Air humidity | ≤ 95 %, Non-condensing |


Classifications

| ECLASS 5.0 | 27243001 |
|------------|----------|
|------------|----------|

| ECLASS 5.1.4 | 27243101 |
|----------------|----------|
| ECLASS 5.1.4 | 27245101 |
| ECLASS 6.0 | 27243101 |
| ECLASS 6.2 | 27243101 |
| ECLASS 7.0 | 27243101 |
| ECLASS 8.0 | 27243101 |
| ECLASS 8.1 | 27243101 |
| ECLASS 9.0 | 27243101 |
| ECLASS 10.0 | 27243101 |
| ECLASS 11.0 | 27243101 |
| ECLASS 12.0 | 27243101 |
| ETIM 5.0 | EC001449 |
| ETIM 6.0 | EC001449 |
| ETIM 7.0 | EC001449 |
| ETIM 8.0 | EC001449 |
| UNSPSC 16.0901 | 32151705 |

Dimensional drawing (Dimensions in mm (inch))

FX0-GETC



Recommended accessories

Other models and accessories → www.sick.com/Flexi_Soft

| | Brief description | Туре | Part no. |
|----------------------------|--|-----------------|----------|
| Others | | | |
| | Sub product family: SIM1000 FX Product category: Programmable devices Supported products: 2D and 3D LiDAR sensors, incremental and absolute encoders, Image-based code readers, Fixed mount barcode scanners, RFID read/write device, displacement measurement sensors, Photoelectric sensors, Flexi Soft main module Processor: Dual-core ARM Cortex-A9 CPU with NEON accelerator Toolkit: SICK algorithm API Further functions: FPGA for I/O handling Connections: Terminal block 1-4, Ethernet, FLEXBUS+ Enclosure rating: IP20 | SIM1000-0P0B110 | 1097817 |
| Safety switching amplifier | | | |
| | Applications: Output expansion module for OSSDs Compatible sensor types: Safety sensors with OSSDs Connection type: Front connector with spring terminals Restart interlock: no External device monitoring (EDM): Via path Outputs: 2 enabling current paths (safe), 1 feedback current path (for use as external device monitoring, not safe) Housing width: 18 mm | RLY3-OSSD100 | 1085343 |
| | Applications: Output expansion module for OSSDs Compatible sensor types: Safety sensors with OSSDs Connection type: Front connector with spring terminals Restart interlock: no External device monitoring (EDM): Via path Outputs: 4 enabling current paths (safe), 1 feedback current path (for use as external device monitoring, not safe), 1 signaling current path (not safe) Housing width: 28 mm | RLY3-OSSD400 | 1099971 |

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

