

# HF transponder, coin RFID transponder

SICK Sensor Intelligence.

RFID

### HF transponder, coin | RFID transponder

RFID



#### Ordering information

Туре	Part no.
HF transponder, coin	6033173

Other models and accessories -> www.sick.com/RFID\_transponder

#### Detailed technical data

#### Features

Туре	Hardtag
Frequency band	HF (13.56 MHz)
Carrier frequency	13.56 MHz
RFID standard	ISO/IEC 15693, ISO/IEC 18000-3 "Mode 1"
Read range	
RFH505	2 cm <sup>1) 2)</sup>
RFH510	3 cm <sup>1) 2)</sup>
RFH515	4.5 cm <sup>1) 2)</sup>
RFH620	6.5 cm <sup>1)</sup>
RFH630	11.5 cm <sup>1)</sup>
Special features	High Temperature
IC type	Texas Instruments Tag-it HF-I
Memory capacity (UII / user memory)	2048 Bit (64 x 4 Byte)
IC write cycle	≤ 100,000
IC data retention time	< 10 years

 $^{1)}\ensuremath{\text{Typical}}\xspace$  value; actual value depends on environmental conditions.

<sup>2)</sup> This transponder can only be read with the RFH5xx, no writing is possible.

#### Mechanics/electronics

Housing material	PPS
Housing color	Black
Enclosure rating	IP68
Weight	+ 1.6 g
Diameter	22 mm
Thickness	3 mm
Design	Round
Mounting method	Recessed

#### Ambient data

Vibration resistance	IEC 68-2-6
Shock resistance	IEC 68-2-27
Ambient operating temperature	-25 °C +90 °C <sup>1)</sup>
Application temperature	+ 130 °C, 50 h, 1 <sup>2)</sup> + 220 °C, 30 s, 1 <sup>2)</sup>
Storage temperature	-40 °C +120 °C

 $^{1)}$  Max. temperature at which the RFID transponder can interact with the RFID read/write device.


 $^{2)}$  Max. temperature the RFID transponder can withstand [maximum temperature; duration; cycles]. For optimal performance, the transponders should completely cool off before a new temperature cycle is started.


CI	lass	ific	ati	ons

ECLASS 5.0	27280402
ECLASS 5.1.4	27280402
ECLASS 6.0	27280402
ECLASS 6.2	27280402
ECLASS 7.0	27280402
ECLASS 8.0	27280402
ECLASS 8.1	27280402
ECLASS 9.0	27280402
ECLASS 10.0	27280402
ECLASS 11.0	27280402
ECLASS 12.0	27280402
ETIM 6.0	EC002998
ETIM 7.0	EC002998
ETIM 8.0	EC002998
UNSPSC 16.0901	52161523

#### Reading field diagram

Reading field diagram RFH63x





RFID

Assembly note





RFID

#### **Recommended services**

Additional services -> www.sick.com/RFID\_transponder

	Туре	Part no.
Commissioning		
<ul> <li>Product area: RFID</li> <li>Range of services: Inspection of connection, alignment, optimization of parameters of the RFU/RFH as well as tests, Setup of previously defined functions of reading configuration, data processing and network, interfaces and inputs and outputs</li> <li>Duration: Additional work will be invoiced separately</li> </ul>	Commissioning RFU/RFH	1610018
Maintenance		
<ul> <li>Product area: RFID</li> <li>Range of services: Inspection, analysis and restoring of defined functions, Checking and adjustment of reading configuration, data processing, network, interfaces and inputs and outputs as well as operating data</li> <li>Duration: Additional work will be invoiced separately</li> </ul>	Maintenance RFU/RFH	1611424

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

### WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

