# IME08-04BNOZTOS

**INDUCTIVE PROXIMITY SENSORS** 



## IME08-04BN0ZT0S | IME

INDUCTIVE PROXIMITY SENSORS





## Detailed technical data

#### Features

Housing	Metric
Housing	Standard design
Thread size	M8 x 1
Diameter	Ø 8 mm
Sensing range S <sub>n</sub>	4 mm
Safe sensing range S <sub>a</sub>	3.24 mm
Installation type	Quasi-flush
Switching frequency	500 Hz
Connection type	Connector M8, 3-pin
Switching output	NPN
Output function	NC
Electrical wiring	DC 3-wire
Enclosure rating	IP67 <sup>1)</sup>
Special features	Quadruple sensing range
Items supplied	Mounting nut, brass, nickel-plated (2x)

<sup>1)</sup> According to EN 60529.

## Mechanics/electronics

Supply voltage	10 V DC 30 V DC
Ripple	≤ 10 %
Voltage drop	$\leq 2 V^{(1)}$

<sup>1)</sup> At I<sub>a</sub> max.

 $^{2)}\ensuremath{\,\text{Supply voltage U}_B}$  and constant ambient temperature Ta.

<sup>3)</sup> Of Sr.

Illustration may differ	

Ordering information

Included in delivery: BEF-MU-M08 (1)

Туре

IME08-04BN0ZT0S

Other models and accessories → www.sick.com/IME

Part no.

1086328

## IME08-04BNOZTOS | IME

INDUCTIVE PROXIMITY SENSORS

Time delay before availability	≤ 50 ms
Hysteresis	1 % 15 %
Reproducibility	$\leq 5 \%^{2)(3)}$
Temperature drift (of S <sub>r</sub> )	± 10 %
EMC	According to EN 60947-5-2
Continuous current l <sub>a</sub>	≤ 200 mA
No load current	≤ 10 mA
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	30 g, 11 ms/10 Hz 55 Hz, 1 mm
Ambient operating temperature	-25 °C +75 °C
Ambient temperature, storage	-25 °C +75 °C
Housing material	Brass, nickel-plated
Sensing face material	Plastic, PA 66
Housing length	50 mm
Thread length	34 mm
Tightening torque, max.	≤ 5 Nm
UL File No.	NRKH.E181493

<sup>1)</sup> At I<sub>a</sub> max.

 $^{2)}\,\mbox{Supply voltage U}_{B}$  and constant ambient temperature Ta.

<sup>3)</sup> Of Sr.

## Safety-related parameters

MTTFD	1,735 years
DC <sub>avg</sub>	0 %
T <sub>M</sub> (mission time)	20 years

#### **Reduction factors**

Note	The values are reference values which may vary
St37 steel (Fe)	1
Stainless steel (V2A, 304)	Approx. 0.75
Aluminum (Al)	Approx. 0.46
Copper (Cu)	Approx. 0.42
Brass (Br)	Approx. 0.56

## Installation note

Remark	Associated graphic see "Installation"
A	4 mm
В	20 mm
c	8 mm
D	12 mm
E	1 mm
F	30 mm

## IME08-04BN0ZT0S | IME


INDUCTIVE PROXIMITY SENSORS

## Classifications

ECLASS 5.0	27270101
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101
ECLASS 6.2	27270101
ECLASS 7.0	27270101
ECLASS 8.0	27270101
ECLASS 8.1	27270101
ECLASS 9.0	27270101
ECLASS 10.0	27270101
ECLASS 11.0	27270101
ECLASS 12.0	27274001
ETIM 5.0	EC002714
ETIM 6.0	EC002714
ETIM 7.0	EC002714
ETIM 8.0	EC002714
UNSPSC 16.0901	39122230


## Installation note

Quasi-flush installation



## **Connection diagram**


Cd-004



INDUCTIVE PROXIMITY SENSORS

## Dimensional drawing (Dimensions in mm (inch))

IME08 Standard, connector, flush



① Connection

② Display LED

③ Fastening nuts (2x); width across 13, metal

#### **Recommended accessories**

Other models and accessories → www.sick.com/IME

	Brief description	Туре	Part no.
Mounting brackets and plates			
	Mounting plate for M8 sensors, steel, zinc coated, without mounting hardware	BEF-WG-M08	5321722
	Mounting bracket for M8 sensors, steel, zinc coated, without mounting hardware	BEF-WN-M08	5321721
Terminal and alignment brackets			
for Cla	Clamping block for round sensors M8, without fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included	BEF-KH-M08	2051477
	Clamping block for round sensors M8, with fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included	BEF-KHF-M08	2051478

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

