IME08-1B5PSZUDKS31

INDUCTIVE PROXIMITY SENSORS



IME08-1B5PSZUDKS31 | IME

INDUCTIVE PROXIMITY SENSORS



Ordering information

Туре	Part no.
IME08-1B5PSZUDKS31	1061643

Included in delivery: BEF-MU-M08 (1)

Other models and accessories → www.sick.com/IME

Illustration may differ



Detailed technical data

Features

Housing	Metric
Housing	Short-body
Thread size	M8 x 1
Diameter	Ø 8 mm
Sensing range S _n	1.5 mm
Safe sensing range S _a	1.215 mm
Installation type	Flush
Switching frequency	4,000 Hz
Connection type	Cable, 3-wire, 6 m
Switching output	PNP
Output function	NO
Electrical wiring	DC 3-wire
Enclosure rating	IP67 ¹⁾
Items supplied	Mounting nut, brass, nickel-plated (2x)

¹⁾ According to EN 60529.

Mechanics/electronics

Supply voltage	10 V DC 30 V DC
Ripple	≤ 10 %
Voltage drop	$\leq 2 V^{(1)}$
Time delay before availability	≤ 100 ms

¹⁾ At I_a max.

 $^{2)}$ Supply voltage U_{B} and constant ambient temperature Ta.

³⁾ Of Sr.

IME08-1B5PSZUDKS31 | IME

INDUCTIVE PROXIMITY SENSORS

Hysteresis	5 % 15 %
Reproducibility	$\leq 2 \%^{(2)(3)}$
Temperature drift (of S _r)	± 10 %
EMC	According to EN 60947-5-2
Continuous current I _a	≤ 200 mA
No load current	≤ 10 mA
Cable material	PUR
Conductor size	0.25 mm ²
Cable diameter	Ø 3.9 mm
Short alread protection	1
Short-circuit protection	*
Power-up pulse protection	 ✓ ✓
Power-up pulse protection	✓
Power-up pulse protection Shock and vibration resistance	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm
Power-up pulse protection Shock and vibration resistance Ambient operating temperature	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm -25 °C +75 °C
Power-up pulse protection Shock and vibration resistance Ambient operating temperature Housing material	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm -25 °C +75 °C Brass, nickel-plated
Power-up pulse protection Shock and vibration resistance Ambient operating temperature Housing material Sensing face material	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm -25 °C +75 °C Brass, nickel-plated Plastic, PA 66
Power-up pulse protection Shock and vibration resistance Ambient operating temperature Housing material Sensing face material Housing length	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm -25 °C +75 °C Brass, nickel-plated Plastic, PA 66 38 mm

¹⁾ At I_a max.

 $^{\rm 2)}$ Supply voltage ${\rm U}_{\rm B}$ and constant ambient temperature Ta.

³⁾ Of Sr.

Safety-related parameters

MTTF _D	1,735 years
DC _{avg}	0 %
T _M (mission time)	20 years

Reduction factors

Note	The values are reference values which may vary
St37 steel (Fe)	1
Stainless steel (V2A, 304)	Approx. 0.8
Aluminum (Al)	Approx. 0.45
Copper (Cu)	Approx. 0.4
Brass (Br)	Approx. 0.4

Installation note

Remark	Associated graphic see "Installation"
В	8 mm
c	8 mm
D	4.5 mm
F	12 mm

IME08-1B5PSZUDKS31 | IME


INDUCTIVE PROXIMITY SENSORS

Classifications

ECLASS 5.0	27270101
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101
ECLASS 6.2	27270101
ECLASS 7.0	27270101
ECLASS 8.0	27270101
ECLASS 8.1	27270101
ECLASS 9.0	27270101
ECLASS 10.0	27270101
ECLASS 11.0	27270101
ECLASS 12.0	27274001
ETIM 5.0	EC002714
ETIM 6.0	EC002714
ETIM 7.0	EC002714
ETIM 8.0	EC002714
UNSPSC 16.0901	39122230


Installation note

Flush installation




Connection diagram

Cd-001



Dimensional drawing (Dimensions in mm (inch))

IME08 Short-body housing, cable, flush



- ① Connection
- ② Display LED
- \bigcirc Fastening nuts (2x); width across 13, metal

Recommended accessories

Other models and accessories → www.sick.com/IME

	Brief description	Туре	Part no.
Mounting bra	ckets and plates		
	Mounting plate for M8 sensors, steel, zinc coated, without mounting hardware	BEF-WG-M08	5321722
	Mounting bracket for M8 sensors, steel, zinc coated, without mounting hardware	BEF-WN-M08	5321721
Terminal and alignment brackets			
	Clamping block for round sensors M8, without fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included	BEF-KH-M08	2051477
	Clamping block for round sensors M8, with fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included	BEF-KHF-M08	2051478

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

