# IME12-04BNOZW6S

**INDUCTIVE PROXIMITY SENSORS** 



## IME12-04BN0ZW6S | IME

INDUCTIVE PROXIMITY SENSORS



#### Ordering information

Туре	Part no.
IME12-04BNOZW6S	1044830

Included in delivery: BEF-MU-M12 (1)

Other models and accessories → www.sick.com/IME

Illustration may differ



#### Detailed technical data

#### Features

Housing	Metric
Housing	Standard design
Thread size	M12 x 1
Diameter	Ø 12 mm
Sensing range S <sub>n</sub>	4 mm
Safe sensing range S <sub>a</sub>	3.24 mm
Installation type	Flush
Switching frequency	2,000 Hz
Connection type	Cable, 3-wire, 10 m
Switching output	NPN
Output function	NC
Electrical wiring	DC 3-wire
Enclosure rating	IP67 <sup>1)</sup>
Items supplied	Mounting nut, brass, nickel-plated (2x)

<sup>1)</sup> According to EN 60529.

#### Mechanics/electronics

Supply voltage	10 V DC 30 V DC
Ripple	≤ 10 %
Voltage drop	$\leq 2 V^{(1)}$
Time delay before availability	≤ 100 ms

<sup>1)</sup> At I<sub>a</sub> max.

 $^{2)}$  Supply voltage  $U_{B}$  and constant ambient temperature Ta.

<sup>3)</sup> Of Sr.

# IME12-04BNOZW6S | IME

INDUCTIVE PROXIMITY SENSORS

Hysteresis	5 % 15 %
Reproducibility	≤ 2 % <sup>2) 3)</sup>
Temperature drift (of S <sub>r</sub> )	± 10 %
EMC	According to EN 60947-5-2
Continuous current l <sub>a</sub>	≤ 200 mA
No load current	≤ 10 mA
Cable material	PVC
Conductor size	0.25 mm <sup>2</sup>
Cable diameter	Ø 3.9 mm
Short-circuit protection	✓
Short-circuit protection Power-up pulse protection	✓ ✓
Power-up pulse protection	✓
Power-up pulse protection Shock and vibration resistance	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm
Power-up pulse protection Shock and vibration resistance Ambient operating temperature	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm -25 °C +75 °C
Power-up pulse protection Shock and vibration resistance Ambient operating temperature Housing material	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm -25 °C +75 °C Brass, nickel-plated
Power-up pulse protection Shock and vibration resistance Ambient operating temperature Housing material Sensing face material	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm -25 °C +75 °C Brass, nickel-plated Plastic, PA 66
Power-up pulse protection Shock and vibration resistance Ambient operating temperature Housing material Sensing face material Housing length	✓ 30 g, 11 ms/10 Hz 55 Hz, 1 mm -25 °C +75 °C Brass, nickel-plated Plastic, PA 66 63 mm

<sup>1)</sup> At I<sub>a</sub> max.

 $^{2)}$  Supply voltage  $U_{\text{B}}$  and constant ambient temperature Ta.

<sup>3)</sup> Of Sr.

### Safety-related parameters

MTTFD	1,735 years
DC <sub>avg</sub>	0 %
Reduction factors	
Note	The values are reference values which may vary
St37 steel (Fe)	1
Stainless steel (V2A, 304)	Approx. 0.8
Aluminum (AI)	Approx. 0.45
Copper (Cu)	Approx. 0.4
Brass (Br)	Approx. 0.4

#### Installation note

Remark	Associated graphic see "Installation"
В	24 mm
c	12 mm
D	12 mm
F	32 mm

#### Classifications

ECLASS 5.0 27270101
---------------------


## IME12-04BNOZW6S | IME

INDUCTIVE PROXIMITY SENSORS

	27270 / 0 /
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101
ECLASS 6.2	27270101
ECLASS 7.0	27270101
ECLASS 8.0	27270101
ECLASS 8.1	27270101
ECLASS 9.0	27270101
ECLASS 10.0	27270101
ECLASS 11.0	27270101
ECLASS 12.0	27274001
ETIM 5.0	EC002714
ETIM 6.0	EC002714
ETIM 7.0	EC002714
ETIM 8.0	EC002714
UNSPSC 16.0901	39122230

#### Installation note

Flush installation




#### Connection type



INDUCTIVE PROXIMITY SENSORS


#### **Connection diagram**

Cd-003



#### Dimensional drawing (Dimensions in mm (inch))

IME12 standard, cable, flush



① Connection

- ② Display LED
- 3 Fastening nuts (2x); width across 17, metal

#### **Recommended accessories**

Other models and accessories → www.sick.com/IME

	Brief description	Туре	Part no.
Mounting bra	ckets and plates		
	Mounting plate for M12 sensors, steel, zinc coated, without mounting hardware	BEF-WG-M12	5321869
40	Mounting bracket for M12 sensors, steel, zinc coated, without mounting hardware	BEF-WN-M12	5308447
Terminal and alignment brackets			
info Cla	Clamping block for round sensors M12, without fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included $% \left( \frac{1}{2}\right) =0$	BEF-KH-M12	2051479
	Clamping block for round sensors M12, with fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included	BEF-KHF-M12	2051480

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

